SIEMENS

Data sheet

3NE3335

SITOR fuse link, with slotted blade contacts, NH2, In: 560 A, aR, Un AC: 1000 V, front indicator



Model	
Product brand name	SENTRON
Product designation	SITOR fuse link
Design of the product	With slotted blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	With blade contacts, silver-plated
Design of the fuse link	SITOR, LV HRC design
General technical data	
	NUA
Size of fuse system / acc. to DIN EN 60269-1	NH2
Operating class of the fuse link	aR
Varying load factor (WL)	1
Supply voltage	
Type of voltage	AC
Current / at AC / rated value	560 A
Supply voltage	
• at AC / rated value	1 000 V
Switching capacity	
Switching capacity current	

• acc. to IEC 60947-2 / rated value	100 kA
Dissipation	
Power loss [W]	95 W
Power loss [W]	
 for rated value of the current / at AC / in hot operating state / per pole 	95 W
• maximum	95 W
Product details	
Product description	Not non-interchangeable
Mechanical Design	
Mounting position	Any, preferably vertical
Environmental conditions	
Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity
Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F
General Product Approval Declaratio Conformit	
	Special Test Certi- Miscellaneous ficate
CCC UR EG-Konf.	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE3335

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NE3335

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE3335

CAx-Online-Generator http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications

