



Fuse-link, 450 A, AC 500 V, 120 kA, NH2, gL/gG, IEC, dual indicator, live gripping lugs



Part no. NH FUSE 450A 500V GG SIZE 2
Catalog No. 450NHG2B

EL-Nummer 1664076
(Norway)

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	450
Rated voltage			AC 500 V
Construction size			NH2
Utilization category			gL/gG
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2
Optional accessories			fuse-holder SD2-D and SD2-S

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			NH2
Rated current		A	450
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No