


DSE M 1 220 FM (971 125)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Spark gap technology particularly suited for use in d.c. circuits
- Directly coordinated with DEHNguard surge protective device without additional cable length



Figure without obligation



Basic circuit diagram DSE M 1 60 FM



Dimension drawing DSE M 1 60 FM

Coordinated and modular single-pole lightning current arrester for d.c. applications; with remote signalling contact for monitoring device (floating changeover contact).

Type Part No.	DSE M 1 220 FM 971 125
SPD classification according to EN 61643-11 / IEC 61643-11	type 1 / class I
Max. continuous operating d.c. voltage (U_C)	220 V
Lightning impulse current (10/350 μ s) (I_{imp})	25 kA
Specific energy (W/R)	156.25 kJ/ohms
Voltage protection level (U_P)	≤ 2.5 kV
Directly coordinated with DEHNguard	DG S 385 FM (Part No. 952 094)
Response time (t_A)	≤ 100 ns
Short-circuit withstand capability for max. mains-side overcurrent protection d.c. (I_{SCCR})	2000 A
Max. mains-side overcurrent protection	250 A gL/gG
Max. backup fuse (DC+/DC- $\rightarrow$ DC+/DC-)	125 A gL/gG
Operating temperature range (parallel connection) (T_{UP})	-40 °C ... +80 °C
Operating temperature range (series connection) (T_{US})	-40 °C ... +60 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (DC+/DC-, DC+/DC-, $\pm$ /DC-) (min.)	10 mm ² solid / flexible
Cross-sectional area (DC+/DC-, $\pm$ /DC-) (max.)	50 mm ² stranded / 35 mm ² flexible
Cross-sectional area (DC+/DC-) (max.)	35 mm ² stranded / 25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Type of remote signalling contact	changeover contact
a.c. switching capacity	250 V / 0.5 A
d.c. switching capacity	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid / flexible
Extended technical data:	used for safety lighting systems
– d.c. and a.c. operation	no
Weight	226 g
Customs tariff number	85363030
GTIN	4013364133648
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.