


## BSP M4 BE 12 (926 322)


- High degree of protection for four single lines
- For installation in conformity with the lightning protection zones concept at the boundaries from  $0_B - 2$  and higher



Figure without obligation



Basic circuit diagram BSP M4 BE 12



Dimension drawing BSP M4 BE 12

Space-saving surge arrester module for protecting four single lines sharing a common reference potential and unbalanced interfaces.

Type	BSP M4 BE 12
Part No.	926 322
SPD class	<span style="border: 1px solid black; padding: 0 2px;">TYPE 2</span> <span style="border: 1px solid black; padding: 0 2px;">PI</span>
Nominal voltage ( $U_N$ )	12 V
Max. continuous operating d.c. voltage ( $U_C$ )	15 V
Max. continuous operating a.c. voltage ( $U_C$ )	10.6 V
Nominal current at 45 °C ( $I_N$ )	0.75 A
C2 Total nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	20 kA
C2 Nominal discharge current (8/20 $\mu$ s) per line ( $I_n$ )	10 kA
Voltage protection level line-line for $I_n$ C2 ( $U_p$ )	$\leq 55$ V
Voltage protection level line-PG for $I_n$ C2 ( $U_p$ )	$\leq 60$ V
Voltage protection level line-line at 1 kV/ $\mu$ s C3 ( $U_p$ )	$\leq 38$ V
Voltage protection level line-PG at 1 kV/ $\mu$ s C3 ( $U_p$ )	$\leq 19$ V
Series impedance per line	1.8 $\Omega$ (s)
Cut-off frequency line-PG ( $f_C$ )	2.7 MHz
Capacitance line-line (C)	$\leq 1.0$ nF
Capacitance line-PG (C)	$\leq 2.0$ nF
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Degree of protection (plugged-in)	IP 20
Pluggable into	BXT BAS / BSP BAS 4 base part
Earthing via	BXT BAS / BSP BAS 4 base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21, UL 497B
SIL classification	up to SIL3 <sup>*)</sup>
Approvals	UL, CSA
Weight	22 g
Customs tariff number	85363010
GTIN	4013364127166
PU	1 pc(s)

<sup>\*)</sup> For more detailed information, please visit [www.dehn-international.com](http://www.dehn-international.com).

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.