

# FRONIUS WATTPILOT

The intelligent charging solution for all electric car drivers that leaves nothing to be desired

With the Fronius Wattpilot, every electric car driver can decide how they would like to charge their car. Charging is extremely affordable in combination with a variable electricity tariff.

The Fronius Wattpilot is available in two versions: the permanently mounted Wattpilot Home for the household and the mobile Wattpilot Go for on the move. The device can be operated using the associated Solar.wattpilot app, which also provides an overview of the charging process at the same time. The intelligent plug and play charging solution has two different charging modes called Eco and Next Trip. What's more, the Wattpilot is PV-optimised, meaning that the car can be charged particularly cost-effectively and sustainably in ampere increments of surplus solar energy.



## TECHNICAL DATA FRONIUS WATTPILOT

| INPUT DATA                      | WATTPILLOT GO 11 J                                       | WATTPILLOT GO 22 J                                       | WATTPILLOT HOME 11 J                             |
|---------------------------------|----------------------------------------------------------|----------------------------------------------------------|--------------------------------------------------|
| Maximum charging power          | 11 kW                                                    | 22 kW                                                    | 11 kW                                            |
| Mains supply types              |                                                          | TT / TN / IT                                             |                                                  |
| Mains connection                | CEE16 plug red 5-pin / 30 cm including neutral conductor | CEE32 plug red 5-pin / 30 cm including neutral conductor | 5-pin cable / 200 cm including neutral conductor |
| Optional adapter set            | CEE32 red fused, CEE blue camping plug, safety plug 16A  | CEE16 red, CEE blue camping plug, safety plug 16A        | —                                                |
| Nominal voltage                 |                                                          | 230 V (1-phase) / 400 V (3-phase)                        |                                                  |
| Nominal current (configurable)  | 6-16A<br>1-phase or 3-phase                              | 6-32A<br>1-phase or 3-phase                              | 6-16A<br>1-phase or 3-phase                      |
| Grid frequency                  |                                                          | 50 Hz                                                    |                                                  |
| Power consumption for standby   |                                                          | 1.9 W (LED not lit), 4.2 W (LED brightly lit)            |                                                  |
| Charging socket                 |                                                          | Type 2 infrastructure socket with mechanical lock        |                                                  |
| Residual current device         |                                                          | 30 mA AC, 6 mA DC                                        |                                                  |
| Supply line cable cross-section | Min. 2.5 mm <sup>2</sup>                                 | Min. 6 mm <sup>2</sup>                                   | Min. 2.5 mm <sup>2</sup>                         |

| GENERAL DATA                              | WATTPILLOT GO 11 J                                                           | WATTPILLOT GO 22 J                                                           | WATTPILLOT HOME 11 J                                                         |
|-------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| PV optimisation                           | Dynamic PV surplus charging from 1.38-11 kW (automatic 1-/3-phase switching) | Dynamic PV surplus charging from 1.38-22 kW (automatic 1-/3-phase switching) | Dynamic PV surplus charging from 1.38-11 kW (automatic 1-/3-phase switching) |
| Network connection                        |                                                                              | WLAN *                                                                       |                                                                              |
| Use                                       |                                                                              | Indoors or outdoors                                                          |                                                                              |
| Type of installation                      |                                                                              | Hanging upright                                                              |                                                                              |
| Protection class                          |                                                                              | IP 54 (IP 44 with type 2 cable plugged in)                                   |                                                                              |
| Standards / guidelines                    |                                                                              | IEC 61851-1, IEC 62196                                                       |                                                                              |
| Dimensions (LxWxH)                        |                                                                              | 25.1 x 14.6 x 9.6 cm                                                         |                                                                              |
| Weight                                    | 1.6 kg                                                                       |                                                                              | 1.9 kg                                                                       |
| Average ambient temperature over 24 hours |                                                                              | Max. 35° C                                                                   |                                                                              |
| Ambient temperature                       |                                                                              | -25 °C to +40 °C (without direct sunlight)                                   |                                                                              |
| Humidity                                  |                                                                              | Between 5% and 95%                                                           |                                                                              |
| Altitude                                  |                                                                              | 0 - 2,000 m                                                                  |                                                                              |
| Impact resistance                         |                                                                              | IK08                                                                         |                                                                              |

\* The Fronius Wattpilot supports WLAN standards 802.11 b/g/n in the 2.4 GHz band with WEP, WPA, WPA2 and WPA3

## SAFETY FUNCTIONS:

- / RFID access control: charging can only be started by selected persons with a valid ID-Chip (RFID).
- / Theft-proof charging socket lock.
- / Additional cable protection can be fitted for the charging box (lock not included in scope of supply): the Wattpilot cannot be removed by simply disconnecting it.
- / Residual current device with direct current detection: 30mA AC, 6mA DC.
- / Phase and voltage testing of the input voltage prevents damage to the charging unit of the electric car if a phase is missing.
- / Auxiliary contact on the relays for checking the switching function (faulty relays are detected).
- / Earthing detection (can be switched off, "Norway function").
- / Three-phase current sensor to evaluate the charging current.
- / Miniature fuse for internal electronics that can be changed by the customer prevents a fault if the supply line is connected incorrectly.
- / Adapter recognition with automatic reduction to 16A (only for Wattpilot Go 22 J).
- / Temperature monitoring: current is reduced if the temperature is too high.

## THE ADVANTAGES AT A GLANCE:

### / Cost-effective charging with variable green electricity tariffs

The electric car can be charged very cheaply from the grid with green electricity through the use of variable green electricity tariffs, particularly at night during low-tariff periods.

### / Standalone app: "Solar.wattpilot"

To operate the Wattpilot, the Solar.wattpilot app (iOS and Android) is available for electric car owners. The device can be put into operation with just a few clicks, charging settings can be made and charging processes visualised.

### / Dynamic PV surplus charging

Dynamic PV surplus charging can be used to charge the electric car with ampere increments of surplus PV by means of 1/3-phase switching. This results in higher self-consumption rates and the PV system paying for itself more quickly.

### / Two different charging modes: Eco and Next Trip

Depending on customer requirements, the electric car can either be charged in an extremely environmentally friendly manner or in a way that is tailored perfectly to the next journey.

### / Network connection via WLAN

### / Can be used anywhere

With the mobile Wattpilot Go, the electric car can be charged anywhere – at home, at work or on holiday.



Check out our  
how-to videos  
on Youtube.

/ Perfect Welding / Solar Energy / Perfect Charging

## THREE BUSINESS UNITS, ONE GOAL: TO SET THE STANDARD THROUGH TECHNOLOGICAL ADVANCEMENT.

What began in 1945 as a one-man operation now sets technological standards in the fields of welding technology, photovoltaics and battery charging. Today, the company has around 5,440 employees worldwide and 1,264 patents for product development show the innovative spirit within the company. Sustainable development means for us to implement environmentally relevant and social aspects equally with economic factors. Our goal has remained constant throughout: to be the innovation leader.

Further information about all Fronius products and our global sales partners and representatives can be found at [www.fronius.com](http://www.fronius.com)

Fronius India Private Limited  
Plot no BG-71/2/B,  
Pimpri Industrial Area,  
MIDC- Bhosari,  
Pune- 411026, India  
[pv-sales-india@fronius.com](mailto:pv-sales-india@fronius.com)  
[www.fronius.in](http://www.fronius.in)

Fronius Australia Pty Ltd.  
90-92 Lambeck Drive  
Tullamarine VIC 3043  
Australia  
[pv-sales-australia@fronius.com](mailto:pv-sales-australia@fronius.com)  
[www.fronius.com.au](http://www.fronius.com.au)

Fronius UK Limited  
Maidstone Road, Kingston  
Milton Keynes, MK10 0BD  
United Kingdom  
[pv-sales-uk@fronius.com](mailto:pv-sales-uk@fronius.com)  
[www.fronius.co.uk](http://www.fronius.co.uk)

Fronius International GmbH  
Froniusplatz 1  
4600 Wels  
Austria  
[pv-sales@fronius.com](mailto:pv-sales@fronius.com)  
[www.fronius.com](http://www.fronius.com)