

Tuotetiedot


Tuotekoodi	VE01-0124	Sähkönumero	3454021	EAN-koodi	6410034540214
Tuotenimi	Taipuisa virtakisko 250A 3x24x800			ETIM-luokka	EC001522
	-				

Tekniset tiedot

	-	
	-	
	-	
	-	
	-	
	-	
	-	
Napaluku	1	kpl
	-	
	-	
	-	
	-	
	-	
	-	
Käyttölämpötila	0	°C
Paino	719	g
IP-suojaus	0	
Standardit	EN 60439-1: 1999/7.3 & 7.6, HD 21.3:1995 + A1: 1999, SFS-käsikirja 154/7.8.2	
Väri / Materiaali	0	
Kiinnitys / KytKentä	0	


Kuvaus

Ounevan TVK on standardin EN 60439-1 ja SFS-käsikirjan 154 kohdan 7.8.2 mukainen taipuisa virtakisko. Kiskot on tarkoitettu jakokeskuksiin sekä erilaisiin sähköasennuksiin, joissa tarvitaan asennukseen helposti taivutettavaa, vähän tilaa vievää kiskoa. Erittäin hyvän joustavuuden ja kestäväen eristeen ansiosta kiskojen pienin taivutussäde on 3 * kokonaispaksuus taivutuskulman ollessa 180°. Eristys on SFS 5523/HD 21.3 mukaista PVC-muovia, ja sitä voidaan käsitellä ja asentaa vielä -15°C:n lämpötilassa.

Mittakuva

Pakkaus

Pakkausmuoto	-	Kpl / Pakkaus	1	Paino [kg]	0,722
Pituus [mm]	800	Leveys [mm]	24	Korkeus [mm]	5

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi

Product data

Product code	VE01-0124	STK-code	3454021	EAN-code	6410034540214
Product name	Flexible busbar TVK 250A 3x24x800mm Cu			ETIM class	EC001522

Technical data


	-	
	-	
	-	
	-	
	-	
	-	
Number of poles	1	pcs
	-	
	-	
	-	
	-	
	-	
	-	
Operating temperature	0	°C
Weight	719	g
IP-protection	0	
Standards	EN 60439-1: 1999	
Color / Material	0	
Mounting / Connection	0	



Description

Flexible busbars conform to the EN-60439-1 standard. Busbars are insulated and designed for distribution boards and electrical installation, which require them to be economic on space and easy to bend. Because of extremely high flexibility and durability of the insulator, the smallest bending radius of the busbar is $3 \cdot \text{total thickness}$ with bending angle of 180° . The material of the insulator is standard PVC so handling and installation is possible even -15°C degrees.

Drawing



Package

Package	-	Pcs / Package	1	Weight [kg]	0,722
Length [mm]	800	Width [mm]	24	Height [mm]	5

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi