OUNEVA
OUNEVA GROUP

TUOTEKORTTI

Tuotetiedot

Tuotekoodi	**VE01-0101**	Sähkönumero	**3454058**	EAN-koodi	**6410034540580**
Tuotenimi	Taipuisa virtakisko 630A 6x40x250			ETIM-luokka	**EC001522**
	-				

Tekniset tiedot

	-	
	-	
	-	
	-	
	-	
	-	
Napaluku	**1**	kpl
	-	
	-	
	-	
	-	
	-	
	-	
Käyttölämpötila	**0**	°C
Paino	**603**	g
IP-suojaus	**0**	
Standardit	**EN 60439-1: 1999/7.3 & 7.6, HD 21.3:1995 + A1: 1999, SFS-käsikirja 154/7.8.2**	
Väri / Materiaali	**0**	
Kiinnitys / Kytkentä	**0**	

CE RoHS

Kuvaus

Ounevan TVK on standardin EN 60439-1 ja SFS-käsikirjan 154 kohdan 7.8.2 mukainen taipuisa virtakisko. Kiskot on tarkoitettu jakokeskuksiin sekä erilaisiin sähköasennuksiin, joissa tarvitaan asennukseen helposti taivutettavaa, vähän tilaa vievää kiskoa. Erittäin hyvän joustavuuden ja kestävän eristeen ansiosta kiskojen pienin taivutussäde on 3 * kokonaispaksuus taivutuskulman ollessa 180°. Eristys on SFS 5523/HD 21.3 mukaista PVC-muovia, ja sitä voidaan käsitellä ja asentaa vielä -15°C:n lämpötilassa.

Mittakuva



Pakkaus

Pakkausmuoto	-	Kpl / Pakkaus	**1**	Paino [kg]	**0,62**
Pituus [mm]	**250**	Leveys [mm]	**40**	Korkeus [mm]	**8**

Ouneva Oy
Teollisuustie 21
FI-82730 Tuupovaara
Finland
Tel. +358 400 179 750
info@ouneva.fi
www.ounevagroup.fi
www.ounevaproducts.fi

OUNEVA
OUNEVA GROUP

PRODUCT CARD

Product data

Product code	**VE01-0101**	STK-code	**3454058**	EAN-code	**6410034540580**
Product name	Flexible busbar TVK 630A 6x40x250mm Cu			ETIM class	**EC001522**
	-				

Technical data

	-	
	-	
	-	
	-	
	-	
	-	
Number of poles	**1**	pcs
	-	
	-	
	-	
	-	
	-	
	-	
Operating temperature	**0**	°C
Weight	**603**	g
IP-protection	**0**	
Standards	**EN 60439-1: 1999/7.3 & 7.6, HD 21.3:1995 + A1: 1999, SFS-käsikirja 154/7.8.2**	
Color / Material	**0**	
Mounting / Connection	**0**	

CE RoHS

Description

Flexible busbars conform to the EN-60439-1 standard. Busbars are insulated and designed for distribution boards and electrical installation, which require them to be economic on space and easy to bend. Because of extremely high flexibility and durability of the insulator, the smallest bending radius of the busbar is 3 * total thickness with bending angle of 180°. The material of the insulator is standard PVC so handling and installation is possible even -15°C degrees.

Drawing



Package

Package	-	Pcs / Package	**1**	Weight [kg]	**0,62**
Length [mm]	**250**	Width [mm]	**40**	Height [mm]	**8**

Ouneva Oy
Teollisuustie 21
FI-82730 Tuupovaara
Finland
Tel. +358 400 179 750
info@ouneva.fi
www.ounevagroup.fi
www.ounevaproducts.fi