


R12-100-/200-/110-/020-



R12-110-230V



1- and 2-pole, 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts: 1 NO, 2 NO, 1 NO a+ 1 NC, 2 NC (closed-circuit current relay, 230V only).
Contact gap 3 mm.

Contact/contact test voltage 2000V and control connections/contact test voltage 4000V.

25A devices XR12. Retrofittable auxiliary contact KM12.

* **Non-standard control voltages:** 42, 48, 60, 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 42, 48, 60, 110 and 220V DC.

R12-100-12V
R12-100-230V
R12-100-8V, 24V, 12V DC, 24V DC
R12-100-*

1 NO 16A
1 NO 16A
1 NO 16A
1 NO 16A

EAN 4010312 200421
EAN 4010312 200445

R12-200-12V
R12-200-230V
R12-200-8V, 24V, 12V DC, 24V DC
R12-200-*

2 NO 16A
2 NO 16A
2 NO 16A
2 NO 16A

EAN 4010312 200506
EAN 4010312 200520

R12-110-12V
R12-110-230V
R12-110-8V, 24V, 12V DC, 24V DC
R12-110-*

1 NO + 1 NC 16A
1 NO + 1 NC 16A
1 NO + 1 NC 16A
1 NO + 1 NC 16A

EAN 4010312 200469
EAN 4010312 200483

R12-020-230V

2 NC 16A

EAN 4010312 201572