


XR12-100-/200-/110-



XR12-110-230V



1- and 2-pole, 25 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts 1 NO, 2 NO, 1 NO + 1 NC.

Contact gap 3 mm.

Contact/contact test voltage 2000 V and control connection/contact test voltage 4000 V.

Retrofittable auxiliary contact KM12.

XR12-100-12V	1 NO 25 A	EAN 4010312 201183
XR12-100-24V	1 NO 25 A	EAN 4010312 201190
XR12-100-230V	1 NO 25 A	EAN 4010312 201206
XR12-100-12V DC	1 NO 25 A	EAN 4010312 203422
XR12-100-24V DC	1 NO 25 A	EAN 4010312 201213
XR12-200-12V	2 NO 25 A	EAN 4010312 201282
XR12-200-24V	2 NO 25 A	EAN 4010312 201299
XR12-200-230V	2 NO 25 A	EAN 4010312 201305
XR12-200-12V DC	2 NO 25 A	EAN 4010312 203446
XR12-200-24V DC	2 NO 25 A	EAN 4010312 201312
XR12-110-12V	1 NO + 1 NC 25 A	EAN 4010312 201237
XR12-110-24V	1 NO + 1 NC 25 A	EAN 4010312 201244
XR12-110-230V	1 NO + 1 NC 25 A	EAN 4010312 201251
XR12-110-12V DC	1 NO + 1 NC 25 A	EAN 4010312 203439
XR12-110-24V DC	1 NO + 1 NC 25 A	EAN 4010312 201268