

Motion detector

HF 3600

EAN 4007841733513



Functional description

Modern architecture places exacting demands both on technology and design. If you want sensors to watch over stairwells or deep rooms discreetly, choosing the HF 3600 is a doubly good decision. To begin with, its stylish, slim-line contours blend into the wall. Then behind it all is cutting-edge technology, quite literally. Because the HF-sensor system instantly responds to any movement - even through glass, wood and stud walls!

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	120 x 78 x 41 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	High frequency
Application, place	Indoors
Type of installation	Surface wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	1,00 – 2,50 m
Optimum mounting height	1,2 m
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Reach, detail	Zur Raumanpassung lassen sich 1 oder 2 Erfassungsrichtungen per Aufkleber ausblenden
Reach, radial	Ø 8 m (50 m²)
Reach, tangential	Ø 8 m (50 m²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 30 min
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	6 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010

<https://www.steinel-professional.de/>

Motion detector

HF 3600

EAN 4007841733513

Manufacturer's Warranty

5 years

Version

white

Motion detector

HF 3600

EAN 4007841733513

Sensorenerfassungsbereich 1

