Motion detectors

IS 240 DUO

black EAN 4007841 602710









1000w

1000 W max.













3 JAHRE HERSTELLER GARANTIE steinel.de/garantie

manufacture's warranty steinel.de/garantie

Function description

Round the corner. Infrared wall sensor IS 240 DUO, for indoors and out, 240° angle of coverage, reach up to 12 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	90 x 60 x 100 mm
Mains power supply	230 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, Outdoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Surface wiring
Switching zones	276 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	1,80 – 4,00 m
Optimum mounting height	2 m
Detection angle	240 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 5 m (52 m ²)

Twilight setting 2 – 2000 lx Time setting 10 s – 15 Min. Switching output 1, resistive 1000 W Switching output 1, number of LEDs 6 pcs. / fluorescent lamps Constant-lighting control No Basic light level function No Settings via Potentiometers With remote control No Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black PU1, EAN 4007841602710	Twilight setting TEACH	No
Switching output 1, resistive 1000 W Switching output 1, number of LEDs 6 pcs. / fluorescent lamps Constant-lighting control No Basic light level function No Settings via Potentiometers With remote control No Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Twilight setting	2 – 2000 lx
Switching output 1, number of LEDs 6 pcs. / fluorescent lamps Constant-lighting control Basic light level function No Settings via Potentiometers With remote control No Interconnection IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty Version No Vo	Time setting	10 s – 15 Min.
Constant-lighting control Basic light level function No Settings via Potentiometers With remote control No Interconnection IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty Version No Vo		
Basic light level function No Settings via Potentiometers With remote control No Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Switching output 1, number of LED / fluorescent lamps	^S 6 pcs.
Settings via Potentiometers With remote control No Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Constant-lighting control	No
With remote control No Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Basic light level function	No
Interconnection No IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Settings via	Potentiometers
IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	With remote control	No
Material Plastic Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Interconnection	No
Ambient temperature -20 - 50 °C Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	IP-rating	IP54
Colour black Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Material	Plastic
Colour, RAL 9005 Manufacturer's Warranty 3 years Version black	Ambient temperature	-20 – 50 °C
Manufacturer's Warranty 3 years Version black	Colour	black
Version black	Colour, RAL	9005
	Manufacturer's Warranty	3 years
PU1, EAN 4007841602710	Version	black
	PU1, EAN	4007841602710

Motion detectors

IS 240 DUO

black EAN 4007841 602710




Accessories

EAN 4007841 630119

Corner wall mount 01

Detection Zone



Mögliche Montagehöhe: 1,80 m – 4,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

