IS 180-2

Silver EAN 4007841 603618









1000w















infrared sensor

max. 12 m

1000 W max.

- 1

2 - 2000 lux

5 sec - 15 mir

Ideal 2 n

acket included

manufacture's warranty steinel.de/garantie

Function description

Homeowner's darling. Infrared wall sensor IS 180-2, for indoors and out, ideal for expansive building fronts and driveways, suitable for corner mounting with corner wall mount, 180° angle of coverage, reach can be set up to 12 m or up to 5 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	120 x 76 x 56 mm
Mains power supply	230 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, Outdoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Surface wiring
Switching zones	504 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	1,80 – 4,00 m
Optimum mounting height	2 m
Detection angle	180 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LED: / fluorescent lamps	^S 6 pcs.
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	Yes
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	Stainless steel
Manufacturer's Warranty	3 years
Version	Silver
PU1, EAN	4007841603618


Motion detectors

IS 180-2

Silver EAN 4007841 603618



Detection Zone



Mögliche Montagehöhe: 1,80 m – 4,00 m Orange: radial Schwarz: tangential

Dimension Drawing

