# **Product Environmental Profile**

#### TeSys Vario - emergency stop switch disconnector







### General information


Reference product	VCCF6
Description of the product	TeSys Vario rotary switch disconnectors act as machine circuit load breakers and can be used for the manual stopping and starting of motors
	Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V and rated current 175A ensuring isolation characterized by rated voltage 8KV. This function is provided for 20 years.

## **心**

#### **Constituent materials**

Reference product mass

1431.2 g including the product, its packaging and additional elements and accessories



Plastics 38.00%
Metals 53.90%
Others 8.10%

### Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <a href="https://www.se.com/ww/en/work/support/green-premium/">https://www.se.com/ww/en/work/support/green-premium/</a>

# (1) Additional environmental information

End Of Life

Recyclability potential:

57%

Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).

### 

Reference service life time	20 years						
Product category	Disconnectors - Low voltage						
Installation elements	Reference VCCF6 does not require any installation operations.						
Use scenario	Load rate: 50% Use time rate (closed unit): 30% of RLT						
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production						
Geographical representativeness	France						
	[A1 - A3]	[A5]	[B6]	[C1 - C4]			
Energy model used	Electricity Mix; Production mix; Low voltage; CZ	Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR			

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Mandatory Indicators			TeSys Vario - emergency stop switch disconnector - VCCF6					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Loads and Benefits
paos maisasos			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	3.42E+02	8.32E+00	1.87E-01	2.02E-01	3.29E+02	3.91E+00	-3.64E+00
Contribution to climate change-fossil	kg CO2 eq	3.40E+02	7.94E+00	1.87E-01	1.93E-01	3.28E+02	3.90E+00	-3.62E+00
Contribution to climate change-biogenic	kg CO2 eq	1.24E+00	3.75E-01	0*	8.99E-03	8.48E-01	4.73E-03	-2.03E-02
Contribution to climate change-land use and land use change	kg CO2 eq	7.90E-08	0*	0*	0*	0*	7.90E-08	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	5.94E-06	1.07E-06	0*	1.34E-08	4.84E-06	1.36E-08	-8.34E-07
Contribution to acidification	mol H+ eq	2.01E+00	9.17E-02	1.20E-03	8.03E-04	1.91E+00	8.53E-03	-2.38E-02
Contribution to eutrophication, freshwater	kg (PO4)³¯ eq	1.59E-02	1.06E-04	0*	0*	1.57E-02	1.69E-04	-1.06E-05
Contribution to eutrophication marine	kg N eq	2.72E-01	7.01E-03	5.65E-04	2.13E-04	2.62E-01	1.56E-03	-2.23E-03
Contribution to eutrophication, terrestrial	mol N eq	3.87E+00	7.34E-02	6.20E-03	1.61E-03	3.77E+00	1.77E-02	-2.45E-02
Contribution to photochemical ozone formation - human health	kg COVNM eq	8.11E-01	2.70E-02	1.57E-03	4.29E-04	7.76E-01	6.00E-03	-8.95E-03
Contribution to resource use, minerals and metals	kg Sb eq	1.09E-03	9.30E-04	0*	0*	1.56E-04	4.82E-06	-7.42E-04
Contribution to resource use, fossils	MJ	6.35E+04	1.44E+02	0*	0*	6.32E+04	1.61E+02	-6.13E+01
Contribution to water use	m3 eq	2.82E+01	3.23E+00	0*	8.64E-02	2.38E+01	1.10E+00	-1.76E+00

Additional indicators for the French regulation are available as well

Inventory flows Indicators TeSys Vario - emergency stop switch disconnector - VCCF6				CCF6				
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits
intenter, none			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	5.85E+03	2.41E+00	0*	0*	5.84E+03	0*	6.71E-01
Contribution to use of renewable primary energy resources used as raw material	MJ	2.20E+00	2.20E+00	0*	0*	0*	0*	-2.00E+00
Contribution to total use of renewable primary energy resources	MJ	5.85E+03	4.61E+00	0*	0*	5.84E+03	0*	-1.33E+00
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.35E+04	1.28E+02	0*	0*	6.32E+04	1.61E+02	-6.13E+01
Contribution to use of non renewable primary energy resources used as raw material	MJ	1.54E+01	1.54E+01	0*	0*	0*	0*	0.00E+00
Contribution to total use of non-renewable primary energy resources	MJ	6.35E+04	1.44E+02	0*	0*	6.32E+04	1.61E+02	-6.13E+01
Contribution to use of secondary material	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of freshwater	m³	6.58E-01	7.52E-02	0*	2.01E-03	5.55E-01	2.55E-02	-4.09E-02
Contribution to hazardous waste disposed	kg	7.82E+01	7.19E+01	0*	0*	4.90E+00	1.40E+00	-5.71E+01
Contribution to non hazardous waste disposed	kg	3.97E+01	6.84E+00	6.56E-03	6.58E-01	3.16E+01	5.66E-01	-4.69E+00
Contribution to radioactive waste disposed	kg	1.58E-02	2.42E-03	4.67E-06	8.83E-05	1.33E-02	2.74E-05	-9.74E-04
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	8.92E-01	0*	0*	1.11E-01	0*	7.80E-01	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00

<sup>\*</sup> represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	ENVPEP2211006_V1	Drafting rules	PEP-PCR-ed4-2021 09 06				
Verifier accreditation N°			PSR-0005-ed2-2016 03 29				
Date of issue	2023/11/14	Intormation and reference documents	www.pep-ecopassport.org				
			5 years				
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016							
Internal X	External						
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (Ddemain)							
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019							
The elements of the present PEP cannot be compared with elements from another program.							
Document in compliance with ISO 14021 : 2016 « Environmental labels and declarations. Type II environmental declarations »							

Schneider Electric Industries SAS
Country Customer Care Center
http://www.se.com/contact
35, rue Joseph Monier
CS 30323
F- 92500 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 928 298 512 €

www.se.com ENVPEP2211006\_V1 Published by Schneider Electric

©2023 - Schneider Electric - All rights reserved

2023/11/14