

End-to-end safety for users and systems

The ideal system protection for every requirement

Safely disconnecting electrical systems from the power grid is essential to protecting humans as well as the systems themselves. We offer you a comprehensive portfolio of SENTRON switching devices for safe, standardcompliant, and efficient switching of electrical equipment. Humans are protected at all times from electrical accidents, and electrical systems are reliably protected from damage. You benefit additionally from a flexible and more productive engineering process.

You need more information about switch disconnectors and transfer switching equipment?

Then feel free to take advantage of our comprehensive support. From planning to commissioning to operation, we're happy to help you at any time.

Technical Support: +49 911 895-5900
support.energy@siemens.com

Information	Planning/ Ordering	Operation/ Service	Training

Siemens SENTRON portfolio of switch disconnectors and transfer switching equipment

	Switch disconnectors					Fuse switch disconnectors		Switch disconnectors with fuses			Transfer switching equipment		
Switching characters													
SETRON Portfolio of switch disconnectors and transfer switching equipment	3KD switch disconnectors	3VA1 switch disconnectors in MCCB design	3LD2 main control and EMERGENCY-STOP switches	3LD3 main control and EMERGENCY-STOP switches	3LD5 UL main control and EMERGENCY-STOP switches 	3NP1 fuse switch disconnectors	3NJ4 fuse switch disconnectors	3KF switch disconnectors with fuses	3KF SITOR switch disconnectors with fuses	3NJ6 switch disconnectors with fuses	Manually operated transfer switching equipment (3KC MTSE)	Remotely operated transfer switching equipment (3KC RTSE)	Automatic transfer switching equipment (3KC ATSE)
Rated current I_n	16 up to 2,000 A	63 up to 250 A	16 up to 250 A	16 up to 63 A	30 up to 150 A	160 up to 630 A	160 up to 2,000 A	32 up to 800 A	32 up to 800 A	160 up to 630 A	16 up to 1,600 A	40 up to 3,200 A	40 up to 3,200 A
Number of poles	3-, 4-, 6-pole	3-, 4-pole	3-, 4-, 6-pole	3-, 4-pole	3-, 4-pole	3-pole	3-pole	3-, 4-pole	3-pole	3-, 4-pole	3-, 4-pole	3-, 4-pole	3-, 4-pole
Max. rated impulse withstand voltage U_{imp}	12 kV	8 kV	6 kV	6 kV	6 kV	8 kV	12 kV	12 kV	12 kV	8 kV	12 kV	12 kV	12 kV
Product standards	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-2, IEC 60947-3, VDE 0660-101, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107, UL508	IEC 60947-3, IEC 60947-1, VDE 0660-107, UL508	UL489, UL 60947-4-1, IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-3, IEC 60947-1, VDE 0660-107	IEC 60947-6-1, IEC 60947-3, VDE 0660-114, VDE 0660-107	IEC 60947-6-1, IEC 60947-3, VDE 0660-114, VDE 0660-107	IEC 60947-6-1, IEC 60947-3, VDE 0660-114, VDE 0660-107
Max. rated conditional short-circuit current	100 kA	2 kA	50 kA	6 kA	65 kA	120 kA	120 kA	100 kA	100 kA	100 kA	100 kA	100 kA	100 kA
Type of electrical connection	Box terminal, flat terminal	Box terminal, flat terminal	Box terminal	Box terminal	Box terminal	Box terminal, flat terminal	Box terminal, flat terminal, V terminal connection, stud connector	Box terminal, flat terminal	Box terminal, flat terminal	Flat terminal, V terminal connection	Box terminal, flat terminal	Box terminal, flat terminal	Box terminal, flat terminal
Switching frequency	<ul style="list-style-type: none"> • for occasional use • for frequent or actuated operation 												
Suitable for fuse links	fuseless	fuseless	fuseless	fuseless	fuseless	NH000 up to NH3 *	NH000 up to NH4 *	NH000 up to NH3 *	SITOR fuse links in LV HRC design NH00 up to NH3 *	NH000 up to NH3 *	fuseless	fuseless	fuseless
Mounting	Floor mounting, standard mounting rail	Floor mounting, standard mounting rail	Floor mounting, front mounting, insulated enclosure with/ without EMC plate	Floor mounting, standard mounting rail, front mounting	Floor mounting, standard mounting rail, front mounting	Floor mounting, standard mounting rail, mounting on busbar systems	Mounting on busbar for 60 mm, 100 mm, 185 mm	Floor mounting, standard mounting rail	Floor mounting, standard mounting rail	Draw-out technology for 185 mm busbar system	Floor mounting, standard mounting rail	Floor mounting, standard mounting rail	Floor mounting, standard mounting rail
Additional information	LV10 Chapter 8	LV10 Chapter 2	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 8	LV10 Chapter 9	LV10 Chapter 9	LV10 Chapter 9



* Applicable fuses for fuse switch disconnectors and switch disconnectors with fuses: NH000 to NH4 / 4a, characteristics gG and aM, 2 to 1,250 A, to AC 690/DC 440 V. Comprehensive range of these and other fuse links as well as fuse holders: LV10 Chapter 5

Possibilities of electrical construction

	Protection without switch function	Switch without protection	Switch (single-counting) with protection function	Switch (double breaker) with protection function	Change	
Product description	Fuse holders and fuse links	Switch disconnectors	Fuse switch disconnectors	Switch disconnectors with fuses	Transfer switching equipment	
Functions	Protection function	✓	-	✓	✓	-
	Switching function	-	✓	✓	✓	✓
	If switching and disconnection is not required	If protection is performed in the higher-level distribution	Occasional switching and protection in one device	Frequent switching and protection in one device	Mains or load switching in one device	
Business areas	Infrastructure – Commercial buildings – Industry					
Example						
	Motor protection	Switching of portable machines (e.g. woodworking machine)	Protection of secondary aggregates for occasional switching (e.g. oil pumps)	Protection and switching of serial machines	Switching between two networks with particularly critical loads (e.g. with additional ATSE bypass)	
Further typical applications	Cable and line protection	OEM and Mechanical engineering	Supply of a control cabinet	Power outlets in motor control centers	Cold stores	
	Converter and soft starter protection (SITOR)	Power disconnector for maintenance purposes	Main fuse in machine connection boxes	Airports and train stations	Pumps	

Published by
Siemens AG 2020

For the U.S. published by
Siemens Industry Inc.

Smart Infrastructure
Electrical Products
Siemensstrasse 10
93055 Regensburg
Germany

Siemens Industry Inc.
100 Technology Drive
Alpharetta, GA 30005
United States

Article No. EMLP-T10215-00-76DE
Printed in Germany
Dispo 25600 • BR 09172.0

Subject to changes and errors.
The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

© Siemens 2020

SIEMENS
Ingenuity for Life

Switch disconnectors
and transfer switch-
ing equipment
Quick Selection Guide

siemens.com/switching-devices