

INSTA contactor 0/1-automatic with 1 NO contact and 1 NC contact
Contact for 230 V AC, 400V 20A Control 230 V AC



Model	
product brand name	SETRON
product designation	Insta contactor
design of the product	1 NO contact 1 NC contact
type of voltage / of the operating voltage	AC
type of voltage / of the operating voltage / for actuation	AC
Supply voltage	
operational current / at AC / rated value	20 A
operating voltage / rated value	
• minimum	250 V
• maximum	250 V
Protection class	
protection class IP	IP20
Switching capacity	
switching capacity active power / with incandescent lamp load	1 000 W
Dissipation	

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole		1.7 W	
Main circuit			
operational current / rated value		20 A	
Control current			
control supply voltage			
• rated value		230 V	
• rated value / maximum		230 V	
Product details			
product component / slide for manual operation		Yes	
number of NC contacts		1	
number of NO contacts		1	
product extension / installable / supplementary devices		Yes	
Mechanical Design			
height		90 mm	
width		18 mm	
depth		71 mm	
installation depth		0 mm	
number of modular width units		1	
net weight		143 g	
Certificates			
reference code			
• acc. to DIN EN 61346-2		Q	
• acc. to IEC 81346-2		Q	
General Product Approval		Declaration of Conformity	Test Certifi- ates
other			
 CCC		 EG-Konf.	
Miscellaneous		Special Test Certi- ficate	Environmental Con- firmations
Further information			
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs			
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5801-6			
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/5TT5801-6			
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5801-6			
CAx-Online-Generator http://www.siemens.com/cax			



