

## OT FIT 60/220-240/12 P

CV Power supplies 12 V



### Product family benefits

- Versatile scope of application due to output power range of up to 300 W
- Very high efficiency
- IP rating: up to IP67
- High surge protection: up to 6 kV (L-N) / 6 kV (L/N-PE)

### Areas of application

- Suitable for indoor and outdoor installations
- Ideal for mounting in very tight spaces

Technical data

Electrical data

Nominal output power	60 W
Mains frequency	50...60 Hz
Nominal voltage	220...240 V
Nominal current	0.36 A
Device power loss	8.6 W
Power factor $\lambda$	0.95 <sup>1)</sup>
Inrush current	45 A <sup>2)</sup>
Nominal output voltage	12.5 V
Input voltage AC	198...264 V
Output ripple Voltage (100 Hz)	< 3 % <sup>3)</sup>

<sup>1)</sup> Typical, Full load, 230 VAC, 50 Hz / 60 Hz

<sup>2)</sup> At Full Load, 240VAC, Cold StartDuration=250uS 50% Ipk–50% Ipk

<sup>3)</sup> ripple @ 100 Hz / full load

Dimensions & weight



Length	157.0 mm
Width	53.0 mm
Height	31.5 mm
Mounting hole spacing, length	153 mm
Mounting hole spacing, width	27.0 mm
Product weight	473.00 g

Temperatures & operating conditions

Ambient temperature range	-40...+50 °C <sup>1)</sup>
Permitted rel. humidity during operation	5...85 % <sup>2)</sup>

<sup>1)</sup> At fullload, Tc not exceeded

<sup>2)</sup> Non-condensing

## Product datasheet

### Additional product data

Predecessor EAN	4008321790811
-----------------	---------------

### Capabilities

Suitable for fixtures with prot. class	I / II
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Dimmable	No
Number of channels	1

### Certificates & standards

Type of protection	IP66/IP67
Standards	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384
Approval marks – approval	CE / CCC / ENEC / TISI / RCM



### Logistical data

Commodity code	850440829000
----------------	--------------

### Environmental information

Date of Declaration	18-11-2021
Primary Article Identifier	4062172133487
Candidate List Substance 1	No declarable substances contained
CAS No. of substance 1	No CAS
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	83225a96-ec66-4d9e-b434-883713d2a5db

### Download Data

File	
	User instruction OPTOTRONIC LED Power Supply
	Declarations of conformity OT FIT 12P CE 4192443 02 130220

## Product datasheet



CAD data 3-dim  
OT FIT 60 220-240 12 P - 3D stp file

### Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172133487	OT FIT 60/220-240/12 P	Shipping carton box 15	349 mm x 224 mm x 153 mm	11.96 dm <sup>3</sup>	7430.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.