

## DALI SWITCH SO

DALI Switch SO | Signal converters for LMS



### Product family features


- DALI-controlled switch output for incandescent lamps, QT, OT, PT, HT control gear
- 3 independent relay contacts
- Load capacity of switching contact: 6 A ohmic load
- Supply voltage: 24 V DC
- Floating contacts

Technical data

Electrical data

Nominal voltage	24.0 V
Mains frequency	0 Hz
System wattage	5.00 W

Dimensions & weight



Length	96.0 mm
Width	54.0 mm
Height	62.0 mm
Product weight	155.00 g

Temperatures & operating conditions

Ambient temperature range	0...+45 °C
---------------------------	------------

Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	3
Load contact	6 A
Type of installation	DIN rail mounting

Certificates & standards

Type of protection	IP20
Protection class	II

Logistical data


Commodity code	853710989900
----------------	--------------

## Product datasheet

### Equipment / Accessories

- Can be used with all DALI control units
- 24 V supply required (e. g. PS 30)

### Download Data

File	
	Declarations of conformity 334856_Declaration of conformity &#150; DALI SWITCH SO

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321533364	DALI SWITCH SO	Shipping carton box 8	250 mm x 89 mm x 208 mm	4.63 dm <sup>3</sup>	1434.24 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Accessories Optional

Product description	Accessory name	Accessory code
DALI SWITCH SO	POWER SUPPLY PS 30	▶ 4052899553880

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.