

CV Power supplies 24 V with 1...10 V



Product family features

- DC mode functionality
- Type of protection: IP66 and IP67
- Surge protection: up to 4 kV (L-N) / 6 kV (L/N-PE)
- Wide operating temperature range: -30...+55 °C
- Lifetime: up to 50,000 h (temperature at max. t_c)
- Dimmable via fully isolated 1...10 V interface

Product family benefits

- Large range of products from 20 W to 250 W
- Installation in very cold and hot environments
- Very stable output power
- High electronical reversible short-circuit, overload, overtemperature protection
- Smart Power Supply: boosting power to turn on cold LEDs
- Independent installation possible
- Dimming range: 1...100 %

Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

Product family datasheet

Technical data

Product description	Electrical data					
	Nominal output power	Mains frequency	Galvanic isolation primary/secondary	Nominal output voltage	Input voltage DC	Input voltage AC
OT 20/220...240/24 DIM P	20 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V
OT 40/220...240/24 DIM P	40 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V
OT 60/220...240/24 DIM P	60 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V
OT 100/220...240/24 DIM P	100 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V
OT 130/220...240/24 DIM P	130 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V
OT 250/220...240/24 DIM P	250 W	0...60 Hz	3 kV	24.2 V	176...276 V	198...264 V

Product description	Dimensions & weight					Temperatures & operating conditions
	Mounting hole spacing, length	Product weight	Length	Width	Height	Permitted rel. humidity during operation
OT 20/220...240/24 DIM P	169.0 mm	315.00 g	178.0 mm	43.0 mm	25.0 mm	5...85 % ¹⁾
OT 40/220...240/24 DIM P	199.0 mm	416.00 g	208.0 mm	43.0 mm	26.0 mm	5...85 % ¹⁾
OT 60/220...240/24 DIM P	199.0 mm	420.00 g	208.0 mm	43.0 mm	26.0 mm	5...85 % ¹⁾
OT 100/220...240/24 DIM P	227.0 mm	765.00 g	240.0 mm	50.0 mm	34.0 mm	5...85 % ¹⁾
OT 130/220...240/24 DIM P	207.0 mm	943.00 g	220.0 mm	63.0 mm	37.0 mm	5...85 % ¹⁾
OT 250/220...240/24 DIM P	250.0 mm	1340.00 g	265.0 mm	68.0 mm	40.0 mm	5...85 % ¹⁾

Product description	Capabilities			
	Suitable for fixtures with prot. class	Overheating protection	Overload protection	Short-circuit protection
OT 20/220...240/24 DIM P	II	Yes	Yes	Yes
OT 40/220...240/24 DIM P	II	Yes	Yes	Yes
OT 60/220...240/24 DIM P	II	Yes	Yes	Yes
OT 100/220...240/24 DIM P	I	Yes	Yes	Yes
OT 130/220...240/24 DIM P	I	Yes	Yes	Yes
OT 250/220...240/24 DIM P	I	Yes	Yes	Yes

Product description	No-load proof	Dimming interface	Dimmable	Number of channels
OT 20/220...240/24 DIM P	Yes	1...10 V	Yes	1
OT 40/220...240/24 DIM P	Yes	1...10 V	Yes	1

Product family datasheet

Product description	No-load proof	Dimming interface	Dimmable	Number of channels
OT 60/220...240/24 DIM P	Yes	1...10 V	Yes	1
OT 100/220...240/24 DIM P	Yes	1...10 V	Yes	1
OT 130/220...240/24 DIM P	Yes	1...10 V	Yes	1
OT 250/220...240/24 DIM P	Yes	1...10 V	Yes	1


Product description	Certificates & standards			Logistical data
	Type of protection	Standards	Approval marks – approval	Commodity code
OT 20/220...240/24 DIM P	IP66	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000
OT 40/220...240/24 DIM P	IP66	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000
OT 60/220...240/24 DIM P	IP66	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000
OT 100/220...240/24 DIM P	IP66/IP67	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000
OT 130/220...240/24 DIM P	IP66/IP67	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000
OT 250/220...240/24 DIM P	IP66/IP67	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384	ENEC / RCM / CCC / EAC	850440829000

¹⁾ Maximum 56 days/year at 85 %

Product family datasheet



OT 20220-24024 DIM P




OT 40220-24024 DIM P




OT 60220-24024 DIM P



OT 100220-24024 DIM P



OT 130220-24024 DIM P



OT 250220-24024 DIM P

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Download Data

File	
	User instruction OPTOTRONIC LED Power Supply
	Addon Technical Information Dimming table for OT (EN)
	Product Datasheet Datasheet OT 20220-24024 DIM P
	Brochures OPTOTRONIC constant-voltage LED power supplies and controls (EN)
	Certificates CCC Certificate No. 2018011002044637
	Certificates CB Test Certificate No. SG PSB-LE-00930
	Certificates ENEC Certificate No. U6 18 01 84117 051
	Declarations of conformity EU Declaration of Conformity 3537796
	Declarations of conformity Attestation of Conformity No. N8A 18 01 84117 055
	Declarations of conformity Attestation of Conformity No. E8A 18 01 84117 050
	Declarations of conformity EU Declaration of Conformity OT 24V P_DIMP
	Product Datasheet Datasheet OT 40220-24024 DIM P
	Certificates CCC Certificate No. 2018011002043864
	Product Datasheet Datasheet OT 60220-24024 DIM P
	Product Datasheet Datasheet OT 100220-24024 DIM P
	Certificates CCC Certificate No. 2018011002043871

Product family datasheet

	Certificates CB Test Certificate No. SG PSB-LE-00906
	Certificates ENEC Certificate No. U6 18 01 84117 048
	Declarations of conformity Attestation of Conformity No. N8A 18 01 84117 054
	Declarations of conformity Attestation of Conformity No. E8A 18 01 84117 049
	Product Datasheet Datasheet OT 130220-24024 DIM P
	Product Datasheet Datasheet OT 250220-24024 DIM P

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899545809	OT 20/220...240/24 DIM P	Shipping carton box 20	334 mm x 277 mm x 186 mm	17.21 dm ³	8116.00 g
4052899545823	OT 40/220...240/24 DIM P	Shipping carton box 20	334 mm x 310 mm x 194 mm	20.09 dm ³	9965.00 g
4052899545847	OT 60/220...240/24 DIM P	Shipping carton box 20	334 mm x 310 mm x 194 mm	20.09 dm ³	10005.00 g
4052899545861	OT 100/220...240/24 DIM P	Shipping carton box 10	384 mm x 324 mm x 134 mm	16.67 dm ³	8884.00 g
4052899545885	OT 130/220...240/24 DIM P	Shipping carton box 10	439 mm x 299 mm x 126 mm	16.54 dm ³	10590.00 g
4052899545908	OT 250/220...240/24 DIM P	Shipping carton box 10	459 mm x 344 mm x 144 mm	22.74 dm ³	14752.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.