


CV Dimmers with 1...10 V

Technical data

Electrical data

Nominal input voltage	10...24 V
Mains frequency	0 Hz
ECG efficiency	96 %
Power loss in stand-by mode	<0.5 W
Nominal output voltage	10.5...24 V
Nominal output power	120 W
Galvanic isolation	SELV equivalent

Dimensions & weight



Mounting hole spacing, length	164.0 mm
Mounting length	164.0 mm
Product weight	81.00 g
Cable cross-section, input side	0.5...1.5 mm ²
Cable cross-section, output side	0.5...1.5 mm ²
Wire preparation length, input side	10 mm
Wire preparation length, output side	10 mm
Length	172.0 mm
Width	42.0 mm
Height	20.0 mm

Colors & materials

Casing material	Plastic
-----------------	---------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	70 °C

Product datasheet

Temperature range at storage	-25...85 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h
--------------	---------

Capabilities

Dimmable	Yes
Dimming interface	1...10 V
Dimming range	0...100 %
Dimming method	Amplitude Modulation / Pulse Width Modulation
Overheating protection	Automatic reversible ¹⁾
Overload protection	Automatic reversible ¹⁾
Short-circuit protection	Automatic reversible ¹⁾
No-load proof	Yes
Suitable for fixtures with prot. class	II
Type of connection, output side	Screw terminal

¹⁾ In combination with OPTOTRONIC power supply

Certificates & standards

Approval marks – approval	CE / UR / VDE / VDE-EMC
Standards	Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61046/Acc. to IEC 61347-2-2/Acc. to UL 508
Type of protection	IP20

Logistical data

Commodity code	853710989900
----------------	--------------

Download Data

File	
	Addon Technical Information 313229_ADDON TECHNICAL INFORMATION OT DIM VS20 OSRAM (GB)
	Brochures OPTOTRONIC constant-voltage LED power supplies and controls (EN)
	Declarations of conformity 334844_Declaration of conformity – OT Dimmer – OT Sequencer

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300943459	OT DIM	Shipping carton box 20	355 mm x 78 mm x 225 mm	6.23 dm ³	1654.20 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.