JIUNGSRAM[™]

Innovation is our heritage EST. 1896



Lightech 60W OT@ LED60CV24EPS GE 97506

Product information

Lightech 60W

- 12V & 24V output.
- High Power Factor & High Efficiency.
- Class II, IP67 Aluminium housing with Side Leads.
- 12V Phase dimming options.
- White case for Signage Applications.

Product data

Product Code	97506
Class II	Yes
ENEC	Yes
SELV	Yes
Product colour	White
Storage Temperature [°C]	-25 / +70
Dimmable	No
Form factor	Aluminum SL
Height [mm]	40
Length [mm]	198
Width [mm]	44
IP	67
Weight [g]	590
IP67	Yes

Performance data

Colour (product colour)	White
Ambient temperature min. [°C]	-25 °C
Ambient temperature max. [°C]	50 °C
Case temperature [°C]	80 °C
Power factor	0.98
Efficiency [%]	87

Electrical data

Input frequency	50/60Hz
Output voltage range	24V
Drive Current [mA]	max 2.5 A
Input voltage range	220-240V
Nominal power [W]	60
Nominal lamp voltage [V]	230

Logistic data

Product status

Marked for phase-out

Disclaimer

This product is intended to be used as a lamp control gear that has to be installed after the mains control switch.



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.