

SLC POWER SUPPLY CV 24V 50W PUSHDIM



50W power supply with built-in PWM-dimmer. PushDim, Mono.

Technical data	
Product ID	S32004
Exterior color	White
Dimming range	1-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
Short circuit protection	Yes
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant voltage	Yes
Dimming phase cut-off	Yes
Dimming phase cut-on	Yes
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	PushDim
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.9
Strain relief	Yes
Frequency range	[50,60] Hz
Input voltage	[100,240] V
Output	
Output current	208 - 2080 mA
Output power	5 - 50 W
Electrical connection (Out)	L`N screw connection
Output type	Constant voltage (CV)
Mono	Yes
Output power per channel	[5,50] W
Max total output power	50 W
Number of LED Output Channels	1
Output voltage	24 - 24 V



06.10.2020

Subject to changes and printing errors

Installation	
Length	210 mm
Height	32 mm
Width	50 mm
Model	Static
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938057202