

SLC POWER SUPPLY CV 24V 100W

PWM PUSHDIM



50W power supply with built-in PWM-dimmer. Dimmable with a simple PushDim switch. Mono.

Technical data	
Product ID	S32006
Exterior color	White
Dimming range	1-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
Short circuit protection	Yes
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	No
Suitable for constant voltage	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	Yes
No dim function	No



Dimming DSI	No
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	PushDim
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.9
Strain relief	Yes
Frequency range	[50,60] Hz
Suitable for DC-voltage (primary side)	No
Input voltage	[100,240] V
Output	
Output power	10 - 100 W
Output type	Constant voltage (CV)
Mono	Yes
Output power per channel	[10,100] W
Max total output power	100 W
Number of LED Output Channels	4
Output voltage	24 - 24 V
Installation	
Length	244 mm
Height	32 mm
Width	64 mm
Model	Static
Suitable for outdoor use	No
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938057219