

SLC POWER SUPPLY CV 24V 100W

DALI DT8 RGBW



Technical data	
Product ID	S32079
DALI version	DALI2
DALI Type	DT8
Number of DALI-address	1
DALI DT8 Color Management Protocol	RGBWAF
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
Short circuit protection	Yes
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	No
Suitable for constant voltage	Yes
Dimming DALI	Yes
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	DALI DT8
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.9
Input voltage	[100,240] V
Strain relief	Yes
Frequency range	[50,60] Hz
Leakage Current	0.5 mA
Output	
RGBW	Yes
Output power	10 - 100 W
Output type	Constant voltage (CV)



RGB	Yes
Output power per channel	[10,100] W
Max total output power	100 W
Output voltage	24 - 24 V
Output current	420 - 4200 mA
Electrical connection (Out)	L`N quick connection
Number of LED Output Channels	4
Installation	
Length	244 mm
Height	32 mm
Width	64 mm
Model	Static
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938060400