

SLC RF TO TRAILING EDGE AC CONTROLLER 1X1,5A



RF to Trailing edge dimmer with strain relief and reliable full isolation design. Minimum brightness setting function.

| Technical data | |
|------------------------------------|----------------------------|
| Product ID | S21008 |
| Exterior color | White |
| Dimming curve (LED) | Logarithmic |
| Dimming range | 0-100% % |
| Operating temperature | -20°C ~ +45°C °C |
| Expected lifetime (Ta 25°C) | 110000 Hours |
| Expected lifetime (Ta 45°C) | 50000 Hours |
| Method of operation | Radio control |
| Colour | White |
| Surface protection | Other |
| Material quality | Other |
| Type of load | Universal and LED Retrofit |
| Material | Plastic |
| Light value memory | Yes |
| Applicable with movement sensor | Yes |
| Applicable with presence indicator | Yes |
| Applicable with time switch/timer | Yes |
| Dimming phase cut-off | Yes |
| Dimming method | Trailing edge |
| Dimming interface | PushDim |
| Input | |
| Nominal voltage | 100 - 240 V |
| Output | |
| Mono | Yes |
| Max total output power | 200 W |
| Installation | |
| Mounting method | Built-in installation |
| Connection type | Screwed terminal |
| Type of fastening | Other |
| Width of device | 45 mm |
| Height of device | 45 mm |
| Depth of device | 21 mm |



06.10.2020

Subject to changes and printing errors

| logistics data | |
|--|---------------|
| Brand | SLC |
| General data | |
| GTIN | 7070938056960 |
| Assembly arrangement | Other |
| Suitable for degree of protection (IP) | IP20 |