



# POWER SUPPLY 60W 24V CV EDXE IP20

- compact LED driver- Constant Voltage (CV)- Electronic short-circuit protection: reversible- protection against "idle"- SELV (Safety Extra Low Voltage)- IP 20

| Technical data                            |                 |
|---|-----------------|
| Product ID                                | S32072          |
| Expected lifetime (Ta 25°C)               | 110000 Hours    |
| Expected lifetime (Ta 45°C)               | 50000 Hours     |
| Protection class                          | II              |
| Housing                                   | Plastic housing |
| Degree of protection (IP)                 | IP20            |
| Suitable for constant current             | No              |
| Suitable for constant voltage             | Yes             |
| Dimming 0-10 V                            | No              |
| Dimming 1-10 V                            | No              |
| Dimming DALI                              | No              |
| Dimming DMX                               | No              |
| Dimming potentiometer (integrated)        | No              |
| Dimming GPRS                              | No              |
| Dimming LineSwitch                        | No              |
| Dimming manufacturer's proprietary system | No              |
| Dimming mains voltage modulation          | No              |
| Dimming phase cut-off                     | No              |
| Dimming phase cut-on                      | No              |
| Dimming programmable                      | No              |
| Dimming RF                                | No              |
| Dimming Sine Wave Reduction               | No              |
| Dimming Touch and Dim                     | No              |
| Dimming Zigbee                            | No              |
| Dimming with push-button                  | No              |
| No dim function                           | Yes             |
| Dimming DSI                               | No              |
| Dimming interface                         | No Dim On/Off   |
| Input                                     |                 |
| Suitable for DC-voltage (primary side)    | No              |
| Output                                    |                 |
| Output power                              | 60 - 60 W       |



06.10.2020

Subject to changes and printing errors

|                                      |                 |
|--------------------------------------|-----------------|
| <b>Output power per channel</b>      | [6,60] W        |
| <b>Max total output power</b>        | 60 W            |
| <b>Number of LED Output Channels</b> | 1               |
| <b>Output voltage</b>                | 24 - 24 V       |
| <b>Installation</b>                  |                 |
| <b>Length</b>                        | 180 mm          |
| <b>Height</b>                        | 30 mm           |
| <b>Width</b>                         | 52 mm           |
| <b>Model</b>                         | Static          |
| <b>Suitable for outdoor use</b>      | No              |
| <b>logistics data</b>                |                 |
| <b>Brand</b>                         | Vossloh Schwabe |
| <b>Imported by</b>                   | The Light Group |
| <b>General data</b>                  |                 |
| <b>GTIN</b>                          | 7070938057394   |