

POWER SUPPLY 75W 24V CV EDXE

IP20



- compact LED driver- Constant Voltage (CV)- Electronic short-circuit protection: reversible- protection against "idle"- SELV (Safety Extra Low Voltage)- IP 20

Technical data	
Product ID	S32073
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	No
Suitable for constant voltage	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	Yes
Dimming DSI	No
Dimming interface	No Dim On/Off
Input	
Suitable for DC-voltage (primary side)	No
Output	
Output power	75 - 75 W



Output power per channel	[7.5,75] W
Max total output power	75 W
Number of LED Output Channels	1
Output voltage	24 - 24 V
Installation	
Length	180 mm
Height	30 mm
Width	52 mm
Model	Static
Suitable for outdoor use	No
logistics data	
Brand	Vossloh Schwabe
Imported by	The Light Group
General data	
GTIN	7070938057400