
## Elena 2W, 2700K

## **Technical data**

Amperage	350mA	
System effect	2W	
Light source	LED	
Colour temperature	2700 Kelvin	
Light intensity	140 Lumen	
Colour rendering	CRI>85	
Expected lifespan	50,000 hours	
Dimmable, how	Depends on driver	
Flicker free	Yes, according to the new Ecodesign / ErP directive (September 2021)	
SVM <0.4	Yes	
PstLM <1	Yes	
SDCM	≤2	
Beam angle	120°	
Carving dimensions	Ø16 mm	
Installation height	34 mm	
Exterior dimensions	Ø33 mm	
Possibility of through wiring	No	
IP-class	IP44 (is intended for installation in areas 1 and 2)	
Insulation class	Class III	
Material	Aluminium	
Environment	Indoors	
Warranty	2 years wtih Nordtronic driver	
Approvals	CE	
250mA 214/ 2700 140		





\*The drawing is not drawn to scale

## **Product information**

- Approved for installation directly in the insulation and flammable materials
- Dimmable with Nordtronic LED driver
- Incl. 3 meter cable with plug
- Quick and easy mounting
- Possibility of mounting in 16 mm flex tube
- Designed and developed in Denmark

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

ltem no.	EAN no.	Colour	Front design
1817	5704629018174	Matt white	Round
1818	5704629018181	Brushed alu	Round
1819	5704629018198	Matt black	Round

## Accessories

ltem no.	EAN no.	Variant
1872	5704629018723	LED Driver dimmable, 5-16W
1883	5704629018839	LED Driver non dimmable, 2-20W
1875	5704629018754	Extention cable 2 m

Please refer to our webpage www.nordtronic.com, where you can find product information, documents, dimming overview etc. All rights reserved by Nordtronic A/S | Flade Engvej 4 | DK-9900 Frederikshavn | Denmark | +45 70 20 95 31