



CE F M M 827 IP20 230 V 50 Hz

- häikäisemätön peilivalaisin
- kiinteään asennukseen, liittimet keskellä valaisinta
- elektroninen liitäntälaitte
- prismaattinen lampunsuojus tuo valoon loistokkuutta
- mukana LUMILUX T5 827 -lamppu



Valaisinhyötysuhde
 $\eta_{LB} = 0.82$



Diagram of a continuous beam with a central support. The left span is labeled "C-0" and the right span is labeled "C-90".

Nimike	Snro	EAN-koodi	VÄRI	W	I [mm]	D [mm]	h [mm]	2 [mm]	
LUMILUX® DECO EL/P									
72161	41 077 36	4050300 356846	valkoinen	8	310	42	54	275	4x1
72165	41 077 45	4050300 356860	valkoinen	13	538	42	54	502	4x1



827 IP20 230 V 50 Hz

- häikäisemätön peilivalaisin
- kiinteään asennukseen, liittimet keskellä valaisinta
- elektroninen liitäntälaite
- opaloitu lampunsuojus vähentää häikäisyä
- mukana LUMILUX T5 827 -lamppu



Valaisinhyötysuhde
 $\eta_{LB} = 0.71$

A diagram of a beam of length 100 units. A central point load labeled 'C-0' is applied at the midpoint. A distributed load labeled 'C-90' is applied over the entire length of the beam, represented by a horizontal line with diagonal hatching underneath.

Nimike	Snro	EAN-koodi	VÄRI	W	l [mm]	b [mm]	h [mm]		
									
72161-44	41 105 02	4050300 497822	valkoinen	8	310	42	54	275	4x1
72165-44	41 105 03	4050300 497846	valkoinen	13	538	42	54	502	4x1