
Sensor-switched outdoor light



EAN 4007841 005535 Article number 005535







## **Function description**

Individualist all round. Outdoor SensorLight L 585 S, ideal for building fronts and entrances, 180° angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor tilts through 70° for exact adjustment of the detection zone.

#### **Technical specifications**

Dimensions (L x W x H)	229 x 215 x 312 mm	Mou
With lamp	No	Slav
Manufacturer's Warranty	3 years	Sne
Settings via	Potentiometers	Cap
With remote control	No	segr Elec
Version	black	Mec
PU1, EAN	4007841005535	Rea
Application, place	Outdoors	Rea
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway	Pho
Installation site	wall	Lam
Impact resistance	IK03	Bas
IP-rating	IP44	Soft
Protection class	II	Twil
Ambient temperature	-20 - 40 °C	Tim
Housing material	Plastic	Bas
Cover material	Glass transparent	Inte

3,00 m
No
Yes
Yes
No
No
r = 3 m (14 m <sup>2</sup> )
r = 10 m (157 m <sup>2</sup> )
Yes
sticker
All-purpose lamp
E27
No
2 – 2000 lx
8 s – 35 Min.
No
No

#### https://www.steinel.de

Subject to technical modifications

01.2023 Page 1 from 3

Sensor-switched outdoor light

# L 585 S

black EAN 4007841 005535 Article number 005535



# **Technical specifications**

Mains power supply	230 – 240 V / 50 Hz	Optimum mounting height	2 m	
Output	60 W			
Power consumption	0,55 W			

## Accessories

EAN 4007841 003548

Replacement glass shade for L 70X/590/535/560/585


Sensor-switched outdoor light



EAN 4007841 005535 Article number 005535




# **Detection Zone**



Mögliche Montagehöhe: 1,80 m – 3,00 m Orange: radial Schwarz: tangential

# Circuit diagram

## **Dimension Drawing**





https://www.steinel.de 01.2023 Page 3 from 3