LED indoor light without sensor - Professional Line

RS PRO P3

warm white
EAN 4007841 056131
Article number 056131

steinel

LED	3000 K					5 years	CE		
30 years (Ø 4,5h / day)	3000K warm-white	IP54	soft light start	connectable with master	energy saving	manufacturer's warranty steinel-professional.de/ garantie	CE	ENEC 10	VDE

Function description

Circular classic. Perfect shape. Perfect efficiency. The perfect indoor light as version without sensor. The RS PRO P3 integrates harmoniously into corridors, hallways and stairwells. It combines timeless design and extremely easy installation with pioneering technology and can be interconnected with the version with sensor by cable. Output: 17,8 W with 2081 lm, 3000 K.

Technical specifications

Dimensions (Ø x H)	400 x 142 mm	Colour temperature	3000 K
With lamp	Yes, STEINEL LED system	Lamp	LED cannot be replaced
With motion detector	No	Base	without
Manufacturer's Warranty	5 years	LED cooling system	Passive Thermo Control
Version	warm white	Soft light start	Yes
PU1, EAN	4007841056131	Interconnection via	Cable
Colour	white	Lebensdauer LED nach IEC-62717 (L70)	100.000 h
Installation site	wall, ceiling	Lebensdauer LED nach IEC-62717 (L80)	74.000 h
Installation	Ceiling	Lebensdauer LED nach IES TM-21 (L70)	>60.000 h
Impact resistance	IK03	Lebensdauer LED nach IES TM-21 (L80)	>60.000 h
IP-rating	IP54	Absicherung B10 (ST)	54
Protection class	II	Absicherung B16 (ST)	87
Ambient temperature	–10 – 40 °C	Absicherung C10 (ST)	90
Housing material	Plastic	Absicherung C16 (ST)	145
Cover material	Plastic, opal	Output	17,8 W
Mains power supply	220 – 240 V / 50 – 60 Hz	Colour Rendering Index CRI	= 82
Luminous flux total product	2081 lm		

RS PRO P3

warm white
EAN 4007841 056131
Article number 056131

steinel

Technical specifications

|			
Total product efficiency	120 lm/W	Photobiological safety in accordance with EN 62471	RG1
		Starting current, maximum	13 A

RS PRO P3

warm white
EAN 4007841 056131
Article number 056131

.● steinel

Dimension Drawing

400

400

142

Light Distribution Curve

150° 180° 150°
120°
90°
60°
30° 0° 30°
50
100
150
200
250

—— C0 / C180   cd / 1000lm   ----- C90 / C270

Output	17,8 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Measured luminos flux (360°)	2081 lm
Colour temperature	3000 K
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

Master circuit diagram

N   L

N

L

Master/slave interconnection circuit diagram

N   L   ↓   N   L

L

N

steinel

Master/slave interconnection circuit diagram