


Orion LED



Orion LED – downlight for LED in aluminium with aluminium reflector.

Description

Recessed downlight with COB LED. Body in diecast aluminium. Reflector in aluminium. White trimring. IP20, 230V, class II.

Application areas

Corridor, common rooms, office, shop, hotel, official environment etc..

Mounting

The fitting is mounted into the ceiling by screw fixing of 3 brackets.

Installation


The fitting is supplied complete with driver and 3 meter cable and plug.

Light source

- 3000K
- 20W = 1600lm
- 30W = 2400lm
- 40W = 3200lm
- RA >80
- Beam angle 60°

Øvrig

Glass decor and support plate for recessing in soft ceiling tiles are available.



Decor clear glass w. frosted brim.

DOWNLIGHT

| Number | Type | Colour | Light source | Control | Weight (kg) |
|---------|------------------|-----------------------------|--------------|---------|-------------|
| 119320 | Orion LED | Hvit | LED 20W 830 | | 1,8 |
| 119321 | Orion LED | Hvit | LED 20W 830 | DALI | 1,8 |
| 119322 | Orion LED | Hvit | LED 30W 830 | | 1,8 |
| 119323 | Orion LED | Hvit | LED 30W 830 | DALI | 1,8 |
| 119324 | Orion LED | Hvit | LED 40W 830 | | 1,8 |
| 119325 | Orion LED | Hvit | LED 40W 830 | DALI | 1,8 |
| 119326 | Dekor | clear glass w. frosted brim | | | |
| 3232144 | Avlastningsplate | | | | |