
Linea 2.3W, 3000K

Technical data

Hole diameter:	Ø63 mm
Height:	11 mm
Front size:	Ø68 mm
Amperage:	350mA
System effect:	2.3W
Light source:	LED 3000 Kelvin
Light intensity:	166 Lumen
Colour rendering:	CRI>90
Beam angle:	100°
IP-class:	IP20
Insulation class:	Class III
Operating temperature:	-10° / +40°
Material:	Downlight: polycarbonat Mounting ring: aluminium


Possibility of through wiring:



No


Product information

- Low height only 11 mm
- CRI>90
- Flicker free
- Incl. mounting ring
- Incl. 2.5 meter cable with plug









*The drawing is not drawn to scale

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

Item no.	EAN no.	Colour	Front design
19111013	5704629001008	Matt white	Round
19111023	5704629001015	Brushed alu	Round

Accessories

Item number	EAN no.	Variant
98514021	5704629001060	LED Driver - not dimmable, 2.5-14W 350mA

Please refer to our webpage www.nordtronic.com, where you can find product information, documents, dimming overview etc. All rights reserved by Nordtronic A/S | Flade Engvej 4 | DK-9900 Frederikshavn | Denmark | +45 70 20 95 31