



Linea kit 3 x 2.3W, 3000K

Technical data for the spots

Hole diameter:	Ø63 mm
Height:	11 mm
Front size:	Ø68 mm
Amperage:	350mA
System effect:	3 x 2.3W
Light source:	LED 3000 Kelvin
Light intensity:	3 x 166 Lumen
Colour rendering:	CRI>90
Beam angle:	100°
Dimmable:	No
IP-class:	IP20
Insulation class:	Class III
Operating temperature:	-10° / +40°
Material:	Downlight: polycarbonat Mounting ring: aluminium
Possibility of through wiring:	No



*The drawing is not drawn to scale

350mA	3x2.3W	3000 Kelvin	166 Lumen	CRI>90			100°	15000 L70B50
	11 mm		IP20		CE	RoHS		

Product information

- Low height only 11 mm
- CRI>90
- Flicker free
- Incl. mounting ring
- Incl. driver for up to 6 spots (6 x 2.3W)
- Incl. 2.5 meter cable with plug
- Switch on 230Vac wire

	This luminaire contains built-in LED lamps.		} LED	
The lamps cannot be changed in the luminaire.				
Nordtronic LED Cabinet light		874/2012		

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

Item no.	EAN no.	Colour	Front design
19112013	5704629001046	Matt white	Round
19112023	5704629001053	Brushed alu	Round