

SLC DL04 R83 BL 700TED 930 IP54 36°



Retracted LED for creating comfortable ambient. Tilt-able (25°) round downlight with smooth design. Suitable for outside use (IP54). Available in black or white.

Light technic	
Product ID	SLC1104
Beam angle	36 °, Medium beam 21-40° °
Colour temperature	3000 K, 3000 - 3000 K
Colour rendering index (CRI/Ra)	90
Type of light source	LED
Efficacy	70 lm/W
Luminous flux (lm)	700
Lamp efficacy	70 lm/W
MacAdam (SDCM)	3
Tilt-able	25 °
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Luminous flux	700 - 700 lm
Rated life time L80/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Type of control signal	Trailing Edge
Exterior color	Black
Dimmable	Yes
Dimming range	1-100% %
Driver output current	230 mA
IP class	IP54
Operating temperature	-10°C ~ +45°C °C
System consumption	10 W
Protection class	II



16.01.2020

Subject to changes and printing errors

Colour housing	Black
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Control gear included	Yes
Max. system power	10 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming phase cut-off	Yes
Power factor	0.9
Dimming method	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC/DC
Strain relief	Yes
Nominal voltage	220 - 240 V
Output	
LED nominal current at constant current	230 - 230 mA
Installation	
Cut-out hole (Ø)	83 mm
Height/depth	55 mm
Built-in width	83 mm
Height	55 mm
Built-in height/depth	55 mm
Length	95 mm
Width	95 mm, 95 mm
Installation depth	55 mm
Type of installation	Recessed
Outer diameter	95 mm
Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Built-in diameter	83 mm
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring

16.01.2020
Subject to changes and printing errors

logistics data	
Pcs carton	48
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938055161
Pallet length	1200 mm
M-pack length	460 mm
Rated power	10 W
F-pack length	111 mm