

QI MOON Ø300 WH 1650LM 830 IP40

110° SENSOR



"Dark Light" Ceiling light with motion sensor and reduced glare due to retractable LEDs. Comes with quick coupler for quick and easy assembly. Not dimmable!



Light technic	
Product ID	3300008
Beam angle	100 °, Extreme wide beam >80° °
Colour temperature	3000 K, 3000 - 3000 K
Efficacy	110 lm/W
Luminous flux (lm)	1650
Glare (UGR)	UGR<23
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Rated luminous flux according to IEC 62722-2-1	1650 lm
Colour of light	White
Rated life time L70/B50 at 25 °C	110000 Hours
Rated life time L80/B10 at 25 °C	50000 Hours
Light distributor	Focal lens
Luminaire efficacy	110 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
CE	Yes
Dimmable	No
RoHs	Yes
Protection class	II
Colour housing	White
With movement sensor	Yes
Type of control gear	Electronic transformer
Material housing	Plastic
Impact strength	IK08
Control gear included	Yes
Max. system power	15 W

26.02.2020
Subject to changes and printing errors

Filament test according to IEC 60695-2-11 650 °C - 30 s

No dim function	Yes
Power factor	0.9
Input	
Nominal voltage	200 - 240 V
Voltage type	AC
Installation	
Height/depth	32 mm
Type of installation	Surface
Outer diameter	300 mm
Conductor cross section	2.5 mm ²
Connection type	Plug clamp
Suitable for wall mounting	Yes
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	Quick Install
Imported by	The Light Group
General data	
M-pack length	330 mm
F-pack length	330 mm