



SLC LED STRIP S2 MONO CV 126 5M 8MM 9,6W 960LM 4000K

08/11/2022

S11065

Product description

Outstanding light output and low power. Suitable for most installations as direct, indirect, decorative and background lighting.

Our bestseller is now available in an upgraded version with better colour rendering CRI 90+, more lumen output and higher efficiency. Suitable for most installations as both direct and indirect lighting. Create uniform light with 126 LEDs pro meter. Must be placed in a profile for cooling and ensure a long lifetime. With double-sided 3M tape, the strip is versatile and easy to mount.



Technical data

Model	Strip
Lamp type	LED not exchangeable
Lamp power per meter	9,6 W
Voltage type	DC
Beam angle	120 °
Rated life time L80/B10 at 25 °C	60000 h
Protection class	II
Colour temperature	4000 - 4000 K
Width	8 mm
Length of particular segments	55,6 mm
Type of wiring	Ending
Conductor cross section	0,35 mm ²



Mounting method	Surface mounting/recessed mounting
Number of nodes per meter	126
Luminous flux per meter	960 lm
Lamp voltage	24 - 24 V
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP54
Colour of light	White
Colour rendering index CRI	90-100
Height/depth	2 mm
Self-adhesive	Yes
Number of poles	2
Connection type	Solder






Colour rendering index (CRI/Ra)	90
LED-Strip length (m)	5
Max length per connection:	5 meter
3M adhesive tape	Yes
Brand	SLC

Beam angle (°)	120
Cutting point, every: (mm)	55
Operating temperature	-20°C ~ +45°C
Dimmable	Yes
Produced by	The Light Group






10mm x 1000mm



C Halfplanes


180.0 0.0
270.0 90.0

Flux 1040 lm
Maximum 324.26 cd/klm
Position C=135.00 G=2.00
Efficiency: 100.00%
Date: 14-10-2020
Asymmetrical



Scandinavian Lighting Concept

S11065



5
kWh/1000h



2019/2015

