

EcoLine Office Recessed 1200 White 3900lm 4000K Ra>80 On/Off

Article code: 9341000617 + 9341000619 / 9341000620
 EAN: 5703821205672 + 5703821205696 / 5703821205702



Electrical

System wattage: 28W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
 Luminous flux: 3900lm
 Efficacy: 139 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B10>50,000
 Light distribution: Direct
 Optic: Double parabolic louvre, satin matt
 UGR: UGR<19

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Sheet steel
 Colour: White (Pure white, 25% gloss)
 Optics: Aluminium

Mounting/Connection

Mounting: Recessed, Indoor
 Module: 1200
 Connection: Screwless terminal block

9341000617/5703821205672 - Housing EcoLine Office Recessed 1200

Dimensions

Length (mm) L: 1200
 Width (mm) W: 142
 Height (mm) H: 63
 Cut-out (mm) L x W: 1215 x 155
 Weight (kg) gross/net: 3,2 / 3,0

9341000619/5703821205696 - Frame and reflector 1300x220

Dimensions

Length (mm) L: 1300
 Width (mm) W: 220
 Height (mm) H: 50
 Weight (kg) gross/net: 2,8 / 2,6

9341000620/5703821205702 - Frame and reflector 1300x280

Dimensions

Length (mm) L: 1300
 Width (mm) W: 280
 Height (mm) H: 50
 Weight (kg) gross/net: 3,2 / 3,0

