


Panel 60*60 | 27W | >130Lm/W | 4000K | UGR<19 | No Dim

Article number: 174-755



This LED panel is suitable for installation in (suspended) ceilings of 60x60 cm. A hanging up method is also possible, using suspension cables or a surface mounting kit (see related products). The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

Features

- High quality external driver with optimum heat regulation
- Flicker-free (1%)
- Plug & Play due connection cable and euro plug
- High light efficiency of >130 Lm/W
- 5 year warranty
- UGR <19 value for minimal discomfort from glare and high productivity

Specifications

Size	60 x 60 cm	CRI value	>80	Height	11 mm
Input voltage	220-240V	UGR value	UGR<19	Cable length	200 cm
Power	27 Watt	Driver	Incl. external Philips Xitanium driver (not dimmable)	Connection type	Europlug
Luminous flux	3717 Lm	Power factor	>0.97	Housing material	Aluminium
Luminous efficiency	>130 Lm/W	Flicker-free	Yes 1%	Housing color	White (powder coating)
Color temperature	4000K	Beam angle	90°	Material diffuser	PMMA (Polymethyl methacrylate)
Light color	Natural white	IP rate	IP20	Lighting method	Edge-lit
Dimming method	Not dimmable	Length	595 mm	Certification mark	CE, RoHS
Lifetime	L80B50 (50.000 hours)	Width	595 mm	Warranty	5 years

