

Panel | Butterfly | 60*60 | Tri-white | UGR<19 | Dim.

Article number: 174-275





This LED panel is suitable for installation in (system) ceilings of 60x60 cm. Typical of this type of LED panel is that it has two slightly tilted surfaces. In addition to giving a different look than a standard surface LED panel, it also reduces possible light nuisance.

Features

- High quality external driver with optimal heat dissipation
- Triac dimmable, flicker-free (<5%)
- Plug & Play by means of power cord and Euro plug
- High light efficiency of >100 Lm/W
- UGR <19 value for less light nuisance and high productivity
- 5 years warranty
- Adjustable by CCT switch in color temperatures 3000K, 4000K and 5700K

Specifications

Size	60 x 60 cm	CRI value	>80	Height	49 mm
Input voltage	220-240V	UGR value	UGR<19	Cable length	200 cm
Power	36 Watt	Driver	Incl. external dimmable driver	Connection type	Europlug
Luminous flux	3000-3600 Lm	Power factor	>0.90	Housing material	Aluminium
Luminous efficiency	>100 Lm/W	Flicker-free	Yes <5%	Housing color	White (powder coating)
Color temperature	Tri-white	Beam angle	90°	Material diffuser	PMMA (Polymethyl methacrylate)
Light color	Warm white, natural white and cold white (3000K, 4000K and 5700K)	IP rate	IP20	Lighting method	Edge-lit
		Length	595 mm	Certification mark	CE, RoHS
		Width	595 mm	Warranty	5 years
Dimming method	Triac				
Lifetime	L80B50 (50.000 hours)				



Line Drawings

