




## NUMINOS® GIMBLE L

white recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1006027                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 25.4 W                  |
| Lumen                             | 2450 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Risk Group                        | 1                       |
| Height                            | 11.5 cm                 |
| Diameter                          | 16 cm                   |
| Net weight                        | 0.6 kg                  |
| Gross weight                      | 0.75 kg                 |
| Shape of cut-out                  | round                   |
| Installation depth                | 11.5 cm                 |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791825 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                                         |
|---------|-------------------------------------------------------------------------|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA for Numi-<br>nos Downlight Serie |
| 1004065 | LED driver , 30W 700mA                                                  |
| 1004070 | LED driver , 40W 700mA                                                  |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse                                        |
| 1004795 | NUMINOS® L , diffuser<br>Prisma                                         |
| 1004796 | NUMINOS® L , diffuser<br>Frosted                                        |
| 1004797 | NUMINOS® L , diffuser<br>Wabe                                           |
| 1006147 | Numinos® L Reducing<br>ring , round 240/150mm<br>black                  |
| 1006148 | Numinos® L Reducing<br>ring , round 240/150mm<br>white                  |
| 1006149 | Numinos® L Reducing<br>ring , square 240/150mm<br>black                 |
| 1006150 | Numinos® L Reducing<br>ring , square 240/150mm<br>white                 |

|                       |         |
|-----------------------|---------|
| Installation diameter | 14.5 cm |
| BIG WHITE Page        | 55      |