



NUMINOS® GIMBLE M

white / black recessed ceiling light, 3000K 55°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1005954
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.5 W
Lumen	1500 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Risk Group	1
Height	9.5 cm
Diameter	13.5 cm
Net weight	0.45 kg
Gross weight	0.55 kg
Shape of cut-out	round
Installation depth	9.5 cm

Light Source

791822	
--------	---

Accessories

1004054	LED driver , 20W 500mA PHASE
1004064	LED driver , 21-29.5W 500/600/700mA
1004069	LED driver , 29W 500mA
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1004792	NUMINOS® M , diffuser Frosted
1004793	NUMINOS® M , diffuser Wabe
1006143	Numinos® M Reducing ring , round 240/120mm black
1006144	Numinos® M Reducing ring , round 240/120mm white
1006145	Numinos® M Reducing ring , square 240/120mm black
1006146	Numinos® M Reducing ring , square 240/120mm white

Installation diameter	12 cm
BIG WHITE Page	53