




NUMINOS® GIMBLE M

black / chrome recessed ceiling light, 2700K 20°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® GIMBLE M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

Item no.	1005923
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.5 W
Lumen	1550 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Risk Group	1
Height	9.5 cm
Diameter	13.5 cm
Net weight	0.45 kg
Gross weight	0.55 kg
Shape of cut-out	round
Installation depth	9.5 cm

Light Source

791800	
--------	---

Accessories

1004054	LED driver , 20W 500mA PHASE
1004064	LED driver , 21-29.5W 500/600/700mA
1004069	LED driver , 29W 500mA
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1004792	NUMINOS® M , diffuser Frosted
1004793	NUMINOS® M , diffuser Wabe
1006143	Numinos® M Reducing ring , round 240/120mm black
1006144	Numinos® M Reducing ring , round 240/120mm white
1006145	Numinos® M Reducing ring , square 240/120mm black
1006146	Numinos® M Reducing ring , square 240/120mm white

Installation diameter	12 cm
BIG WHITE Page	53