Neptune 002 - half cover LED



ED

Œ



Neptune 002 with LED light source and sensor

Description

Neptune is a quality fitting in an oval shape (002) made of high pressure die-cast aluminium. Diffuser in UV- and vandal resistant polycarbonate. The front ring is fixed with 4 torx screws in stainless steel which are given a Delta seal treatment. IP65 class I. House number plate available as accessorie. The plate is fixed together with the fitting from behind.

Application areas

P-house, facades, entrances, stairs, pedestrian areas, underpasses and tunnels.

Mounting

Direct in ceiling or on wall.

Installation

The fitting is prepared both for open and hidden installation. Push in terminal block 3x2x2,5 mm² with through-wiring possibilities.

Light source

- 1100 lm 3000 K 12W
- 1100 lm 4000 K 12W
- Life time 50.000 hours
- Light level equal to 26W compact lamp

Additional

The sensibility is adjusted on the microwave sensor. Likewise the hold time (exposure time after detected movement) might be adjusted (5 sek - 25 min). The sensor has also a setting for a twilight function (2 - 30 lux). Classic Detect can also be used as Master for other fittings.

Number	Туре	Decor	Diffuser	Colour	Light source	Weight (kg)
			. .			
111884	Neptune 002	Half cover	Opal	White	LED 840 1x12W	1,9
111885	Neptune 002	Half cover	Opal	Black	LED 840 1x12W	1,9
111882	Neptune 002	Half cover	Opal	White	LED 830 1x12W	1,9
111883	Neptune 002	Half cover	Opal	Black	LED 830 1x12W	1,9
111896	Neptune 002 detect	Half cover	Opal	White	LED 840 1x12W	2,0
111897	Neptune 002 detect	Half cover	Opal	Black	LED 840 1x12W	2,0
111894	Neptune 002 detect	Half cover	Opal	White	LED 830 1x12W	2,0
111895	Neptune 002 detect	Half cover	Opal	Black	LED 830 1x12W	2,0

NB! A microwave sensor detect all forms of movement, not only from people and animals. This means that the sensor might detect movements for instance from branches or leaves. Please allow for this when installing the fitting to awoid unwanted functions.