

RS PRO S10 SC

PC warm white

EAN 4007841 081096

Article number 081096



LED

36 years (Ø 4,5h / day)



indoor light

3000 K

3000K warm-white



high frequency sensor 360°



max. 8 m



2 - 2000 lux



connectable via bluetooth



Light source not exchangeable



Control gear not exchangeable



IK07

Function description

Intelligence is not a question of size. It's a question of inner values. The smartest luminaire in the world, now even better! High-frequency sensor luminaire RS PRO S-series, ideal for office corridors, hallways, toilet facilities, stairwells, including radio networking with other RS PRO S-series, 9,1 W LED, 858 lm, PC cover, 3000 K, 360° detection, range Ø 1 - 8 m continuously adjustable, basic light function, and neighbourhood group function. The S-series can also be operated with direct current, which enables connection to central battery systems.

Technical specifications

Dimensions (Ø x H)	300 x 71 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	App, Connect Bluetooth Mesh
Version	PC warm white
PU1, EAN	4007841081096
Application, place	Indoors
Application, room	corridor / aisle, function room / ancillary room, Indoors, multi-storey / underground car park, reception / lobby
Colour	Silver
Installation site	wall, ceiling
Installation	Surface wiring, Ceiling, Wall
Impact resistance	IK07
IP-rating	IP20

Luminous flux total product	858 lm
Total product efficiency	94 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
Functions	Motions sensor, Adjustable fade time when switching on and off, DIM function, Free selection of the light value in a luminaire group, Group parameterisation, Semi-/fully automatic, Light sensor, Neighbouring group function, Normal / test mode, Orientation light, Presence detector logic, Encrypted communication
Twilight setting	2 - 2000 lx
Time setting	5 s - 60 Min.

RS PRO S10 SC

PC warm white

EAN 4007841 081096

Article number 081096



Technical specifications

Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	PC, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Power consumption	0,38 W
Mounting height max.	4,00 m
HF-system	5,8 GHz
Slave modeselectable	Yes
Detection	also through glass, wood and stud walls
Angle of aperture	160 °
Electronic scalability	Yes
Reach, radial	Ø 8 m (50 m ²)
Reach, tangential	Ø 8 m (50 m ²)
Photo-cell controller	Yes
Transmitter power	< 1 mW

Basic light level function	Yes
Basic light level function, detail	LED effect light
Basic light level function time	1-60 min, all night
Main light adjustable	Yes
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth Mesh Connect
Lebensdauer LED nach IEC-62717 (L70)	100.000 h
Lebensdauer LED nach IEC-62717 (L80)	69.000 h
Lebensdauer LED nach IES TM-21 (L70)	>60.000 h
Lebensdauer LED nach IES TM-21 (L80)	>60.000 h
Absicherung B10 (ST)	46
Absicherung B16 (ST)	74
Absicherung C10 (ST)	77
Absicherung C16 (ST)	122
Basic light level function in per cent	7 – 100 %
Output	9,1 W
Colour Rendering Index CRI	= 82

RS PRO S10 SC


PC warm white

EAN 4007841 081096

Article number 081096




Detection Zone




Mögliche Montagehöhe: 2,00 m – 4,00 m
Orange: radial und tangential

Dimension Drawing



Slave/wireless master interconnection circuit diagram



Master/master interconnection circuit diagram

