



LedgeCircle - innovative and discreet design - energy efficient and installation friendly

Description

LedgeCircle is a robust and decorative robust and decorative all-purpose fitting for both private and official use. Body partly in composite and die-cast aluminium-RAL 9016. Diffuser in opal UV- stabilized and impact resistant polycarbonate.

Application area

All-purpose lighting in entrances, staircases, corridors, waiting areas, toilets, bathrooms etc...

Mounting

Direct in ceiling or on wall. Two key-holes adapted standard ceiling and wall boxes. Distance rings are enclosed for use if surface cabling.

LED unit

Effect fitting	29W	29W
Colour temperature	3000K	4000K
Luminous flux fitting - lm	2900	2900
Luminous efficiency fitting - lm/W	100	100
Colour index - RA	>80	>80
Colour tolerance - MacAdam	3	3
Ambient temperature - Ta	25°	25°
Life time LED - LxxBxx - hours:	50.000	50.000
Life time Driver - hours	50.000	50.000

Installation

Supplied with quick-connector between the mounting plate and the fitting.(more info will follow).

Sensor

Detect versions supplied with build-in microwave sensor with an OnOff function responding on movements in the surrounding of the fitting. The sensitivity can be adjusted directly on the sensor.

PIR version (details will follow).

Dimming

Dimming with trailing edge dimmers. (more information will follow).



LedgeCircle without sensor



LedgeCircle with sensor

CEILING - WALL

3000K	4000K	Type	Colour	Light source	Control	Weight (kg)
120783	120788	LedgeCircle Opal D460	White	29W	No	
120784	120789	LedgeCircle Opal D460	White	29W	DALI	
120785	120790	LedgeCircle PIR Opal D460	White	29W	OnOff	
120786	120791	LedgeCircle PIR Opal D460	White	29W	MinMax	
120787	120792	LedgeCircle PIR Opal D460	White	29W	MinMaxOff	
		LedgeCircle Detect Opal D460	White	29W	MinMaxOff	

Reservation for misprinting or product changes.