




Ecotale SPS4-PL600x600-DIM LED Panel

Product	SPS4-PL600x600-DIM
LED Power	40 W
LED	SMD3014
LED Quantity	308
Luminous flux (Ta < 25°C)	WW 2900 lm, NW 2900 lm, CW 3100 lm
Cover	Opal Acrylic
Connection	AC 230 V
Operation voltage	Dimming power supply (1-10 V) AC 200-240 V / 50-60 Hz
Power factor	> 0.9
Color temperature (range)	Warm white WW 3000K (3000-3500K) Natural white NW 4000K (4000-4500K) Cool white CW 5500K (5500-6500K)
CRI	70-80 Ra
Beam angle	110°
Lifetime	50.000 h
Lumen maintenance	70 % of luminous flux left after lifetime (Ta < 25°C)
Warranty	3 years (5 years optional)
Operating temperature	-40°C – +50°C
Operating humidity	10 – 85 %
Housing protection rating	IP20 (IP44 optional)
Housing materials	Aluminum
Product dimensions (L x W x H)	595 mm x 595 mm x 9.7 mm
Weight	3.4 kg
Pieces per pack / Packs per outerbox	1 / 3
Electrical number	IP20: 42 477 05 (3000K), 42 477 15 (4000K) IP44: 42 477 25 (4000K)

