




Tyyppi	Tuotenimi	A	D	E	F
AL140 - ilman varusteita					
AL14011	AL14011 IP44 TC-S 11W	335	178	190	58
AL14015	AL14015 IP44 T8 15W	475	273	400	44
AL14018	AL14018 IP44 T8 18W	628	196	503	63
AL14036	AL14036 IP44 T8 36W	1237	520	630	303
AL14014	AL14014 IP44 T5 14W	585	196	510	38
AL14021	AL14021 IP44 T5 21W	885	408	602	74
AL14028	AL14028 IP44 T5 28W	1186	386	850	254
AL141 - suojakumipäällysteinen kytkin					
AL14111	AL14111 IP44 TC-S 11W KYTKIN	335	178	190	58
AL14115	AL14115 IP44 T8 15W KYTKIN	475	273	400	44
AL14118	AL14118 IP44 T8 18W KYTKIN	628	196	503	63
AL14136	AL14136 IP44 T8 36W KYTKIN	1237	520	630	303
AL14114	AL14114 IP44 T5 14W KYTKIN	585	196	510	38
AL14121	AL14121 IP44 T5 21W KYTKIN	885	408	602	74
AL14128	AL14128 IP44 T5 28W KYTKIN	1186	386	850	254
AL142 - 2-os. pistorasia ja suojakumipääll. kytkin					
AL14211	AL14211 IP44 TC-S 11W 2-OS PR	521	364	190	245
AL14215	AL14215 IP44 T8 15W 2-OS PR	661	362	400	231
AL14218	AL14218 IP44 T8 18W 2-OS PR	814	365	480	231
AL14236	AL14236 IP44 T8 36W 2-OS PR	1423	520	818	303
AL14214	AL14214 IP44 T5 14W 2-OS PR	771	363	510	226
AL14221	AL14221 IP44 T5 21W 2-OS PR	1071	548	670	178
AL14228	AL14228 IP44 T5 28W 2-OS PR	1372	386	850	254
AL142 - 2-os. pistorasia ja suojakumipääll. kytkin, harmaa					
ALH14211	ALH14211 TC-S 11W 2-OS PR HA	521	364	190	245
ALH14215	ALH14215 T8 15W 2-OS PR HA	661	362	400	231
ALH14218	ALH14218 T8 18W 2-OS PR HA	814	365	480	231
ALH14214	ALH14214 IP44 T5 14W 2-OS PR	771	363	510	226
ALH14221	ALH14221 IP44 T5 21W 2-OS PR	1071	548	670	178
ALH14228	ALH14228 IP44 T5 28W 2-OS PR	1372	386	850	254
AL142 - 2-os. pistorasia, suojakumipääll. kytkin, modulimittaiset (AL = valkoinen, ALH = harmaa)					
AL14229MOD	AL14229MOD IP44 TC-S2X9W 2 PR	597	392	296	244
ALH14229MOD	ALH14229MOD IP44 TC-S2X9W 2 PR	597	392	296	244
AL142 - 1-os. pistorasia, suojakumipääll. kytkin vikavirtasuojalla (AL = valkoinen, ALH = harmaa)					
AL14229V	AL14229V IP44 TC-S2X9W 1PR RCB	597	392	296	244
ALH14229V	ALH14229V TC-S2X9W 1PR RCB HA	597	392	296	244
AL143 - 1-os. pistorasia					
AL14314	AL14314 IP44 T5 14W 1-OS PR	670	260	500	125
AL140 ja AL142 Philips MASTER LEDtube tai vastaavalla LED- valonlähteellä					
AL140L11	AL140L11 IP44 11W/840 628MM	628	196	503	63
AL140L22	AL140L22 IP44 22W/840 1237MM	1237	520	630	303
AL142L11	AL142L11 IP44 11W/840 2P 814MM	814	365	480	231
AL142L22	AL142L22 IP44 22W/840 2P1423MM	1423	520	818	303