# REC

ARKOSLIGHT®

DIMENSIONS

58

110

354

CE

Rec is a LED appliance that is especially ideal to carry out wall washer functions or, even, for ceilings –thanks to its considerable luminous flux-. This is a luminary that perfectly fits into projects that prioritise the comfort given by indirect lighting but also require a high volume of light. The illumination distribution on the wall draws a boundary-line between the shaded and illuminated area. Formally, Rec is expressed in a slender cuboid with pure lines and a minimalist design.

10-12-18 / 15:44

3 Year GUARANTEE*
UPGRADEABLE TO 5
UNDER SPECIAL
GUARANTEE CONDITIONS

LIGHTING TECHNICAL DATA

ARKOSLIGHT®

POLAR DIAGRAM

cd/klm

η = 76%

— C0 - C180   — C90 - C270

CONICAL DIAGRAM

Distance [m]	Cone Diameter [m]		Illuminance [lx]
1.0	2.32	E(0°)	531
	2.61	E(C90) 49.2°	75
		E(C0) 52.5°	60
2.0	4.63	E(0°)	133
	5.21	E(C90) 49.2°	19
		E(C0) 52.5°	15
3.0	6.95	E(0°)	59
	7.82	E(C90) 49.2°	8
		E(C0) 52.5°	7
4.0	9.27	E(0°)	33
	10.43	E(C90) 49.2°	5
		E(C0) 52.5°	4
5.0	11.59	E(0°)	21
	13.03	E(C90) 49.2°	3
		E(C0) 52.5°	2

— C0 - C180 (Half-value Angle: 105.0°)
— C90 - C270 (Half-value Angle: 98.4°)

3Year GUARANTEE*

UPGRADEABLE TO 5
UNDER SPECIAL
GUARANTEE CONDITIONS