




		P	CCT	I	Flux	LOR
SWAP M CRI>90	A212-21-10- W R G Z WN N W54	5W	2700K	150mA	675Lm	86%
	A212-21-11- W R G Z WN N W54	5W	3000K	150mA	700Lm	86%
	A212-21-12- W R G Z WN N W54	5W	4000K	150mA	710Lm	86%
	A212-22-10- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-22-11- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	A212-22-12- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%
	A212-22-20- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-22-21- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	PHASE CUT** A212-22-22- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%
	A212-22-30- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-22-31- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	DALI I PUSH** A212-22-32- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%

SWAP M Super CRI CRI>97	A312-22-10- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-22-11- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	A312-22-12- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%
	A312-22-20- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-22-21- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	PHASE CUT** A312-22-22- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%
	A312-22-30- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-22-31- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	DALI I PUSH** A312-22-32- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%

LED	220 240 V~	01	CE	IP20	IP54*	L80B10 > 60.000 h	MacAdam Step 2	FAST CONNEC	INCL	INCL ACC.	Ø75	UGR <19	42°
-----	---------------	----	----	------	-------	----------------------	-------------------	---------------	------	-------------	-----	---------	-----

		P	CCT	I	Flux	LOR
SWAP M DIM to warm CRI>90	A212-23-39- W R G Z WN N W54	6W	3000-1800K	350mA	640Lm	80%

LED	220 240 V~	01	CE	IP20	IP54*	L80B20 > 55.000 h	MacAdam Step 3	FAST CONNEC	INCL	INCL ACC.	Ø75	UGR <19	42°
-----	---------------	----	----	------	-------	----------------------	-------------------	---------------	------	-------------	-----	---------	-----



*Swap IP54

NOT COMPATIBLE WITH EXTRA BEZEL | AFFECTS THE LIGHTING PARAMETERS

DIRECT REFERENCE	LOR
W54 ☐	81%
W54 ☐ DIM TO WARM	76%

OTHER COLOURS

REFERENCE + A212-20-54	IP54 ACCESSORY M
------------------------	------------------

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR	W ☐ R ☐ G ☐ Z ☐ WN ☐ N ☐	MATERIAL	AL ☐ PC ☐ PC ☐	RAL	» 365
--------	--	----------	---	-----	-------

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» PLEASE CONSULT