



		P	CCT	I	Flux	LOR
SWAP XL CRI>90	A212-41-10- W R G Z WN N W54	5W	2700K	150mA	675Lm	86%
	A212-41-11- W R G Z WN N W54	5W	3000K	150mA	700Lm	86%
	A212-41-12- W R G Z WN N W54	5W	4000K	150mA	710Lm	86%
	A212-42-10- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-42-11- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	A212-42-12- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%
	A212-42-20- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-42-21- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	PHASE CUT** A212-42-22- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%
	A212-42-30- W R G Z WN N W54	7W	2700K	200mA	910Lm	86%
	A212-42-31- W R G Z WN N W54	7W	3000K	200mA	940Lm	86%
	DALI I PUSH** A212-42-32- W R G Z WN N W54	7W	4000K	200mA	960Lm	86%

SWAP XL Super CRI CRI>97	A312-42-10- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-42-11- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	A312-42-12- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%
	A312-42-20- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-42-21- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	PHASE CUT** A312-42-22- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%
	A312-42-30- W R G Z WN N W54	7W	2700K	200mA	770Lm	86%
	A312-42-31- W R G Z WN N W54	7W	3000K	200mA	800Lm	86%
	DALI I PUSH** A312-42-32- W R G Z WN N W54	7W	4000K	200mA	820Lm	86%

LED

220
240 V~

CE

IP20

IP54*

L80B10
> 60.000 h

MacAdam
Step 2

FAST | CONNec

INCL


INCL | ACC.

Ø101

UGR <19

43°

					P	CCT	I	Flux	LOR												
SWAP XL																					
DIM to warm																					
CRI>90																					
DALI I PUSH**					A212-43-39- W R G Z WN N W54	6W	3000-1800K	350mA	640Lm	80%											
LED	220 240 V~		CE		IP20	IP54*	L80B20 > 55.000 h		MacAdam Step 3		FAST CONNec		INCL		INCL ACC.		Ø101		UGR <19		43°



*Swap IP54	
NOT COMPATIBLE WITH EXTRA BEZEL AFFECTS THE LIGHTING PARAMETERS	
DIRECT REFERENCE	LOR
W54 ☐	81%
W54 ☐ DIM TO WARM	76%

OTHER COLOURS

REFERENCE + A212-40-54 IP54 ACCESSORY XL

PRE-ASSEMBLED. NOT SOLD SEPARATELY

IP20

EXCL | ACC.

46°

IP54